



PAX® Process Input Panel Meter, AC-Powered

Item number: PAXP0000

The AC-Powered PAX® Process Input Panel Meter helps you visualize analog and digital inputs with reliable panel meters that save you money and reduce downtime. When requirements change, simply upgrade your meter with field-installable, plug-and-play option cards to add communication, programming, I/O and setpoint capability.



Visualize and control industrial processes with a field-upgradable panel meter

Features and benefits

- ✓ **Recognized as an industrial standard**
For 23 years, the PAX Meter has been voted North America's number 1 panel meter by Control Design's readers.
- ✓ **Compact, easy to read display**
Visualize critical performance data easily on a 5-digit 0.56" (14 mm) red sunlight readable LED display.
- ✓ **Field-upgradable communications and programming cards**
Add communications or programming capability with optional cards. Choose from RS232, RS485, Modbus®, PROFIBUS-DP and Crimson® programming.
- ✓ **Field-upgradable setpoint cards**
Add setpoint capability with optional cards. Choose from dual relay, quad relay, quad sinking and quad sourcing.
- ✓ **Runs on AC power.**
Uses 85-250 AC.
- ✓ **Visualize any analog parameter**
Whatever parameter you need to monitor, the PAX series covers it. Keep track of process inputs.
- ✓ **Customizable units for evolving demands**
When needs change, upgrade your meter instead of replacing it. A label kit and plug-and-play option cards add new capabilities. Choose from programming, communication, analog output and setpoint cards.
- ✓ **Field-upgradable analog output cards**
Install a single analog output card for 0 to 20 mA, 4 to 20 mA or 0 to 10 VDC
- ✓ **Custom unit labels**
Identify your display with one of 189 different engineering units available with the label kit accessory.
- ✓ **Agency Approved**
UL listed



PAX® Process Input Panel Meter, AC-Powered

General

| | |
|-----------------------------------|--|
| Net Weight (g) | 295 |
| Packed Width (mm) | 152.4 |
| Packed Height (mm) | 101.6 |
| Packed Depth (mm) | 203.2 |
| Packed Weight (g) | 295 |
| Operating Temperature °C Min | 0 |
| Operating Temperature °C Max | 50 |
| Storage Temperature °C Min | -40 |
| Storage Temperature °C Max | 60 |
| Relative Humidity | 0 to 85% relative humidity (non-condensing) |
| Input Voltage (V) | 85 to 250 VAC |
| Maximum Installation Altitude (m) | 2000 |
| Mounting | DIN rail mount (bracket included), Panel mount |
| Panel Cut-Out Dimensions | 3.62" (92 mm) x 1.77" (45 mm) |
| Housing Materials | Polycarbonate |
| Front Sealing | NEMA 4X/IP65 outdoor |
| Back Sealing | IP20 |
| Packaging Material | Cardboard |
| Warranty (years) | 2 |

PAX® Process Input Panel Meter, AC-Powered



Identification and Status

| | |
|---|--------------------------------|
| Product ID | PAXP0000 |
| Country of Origin | United States of America (the) |
| HS Code | 9030337000 |
| Dual Usage | No |
| Export Control Classification Number (ECCN) | EAR99 |

Physical Features

| | |
|-----------------------------|----------|
| Connectors / Input / Output | Terminal |
| SD Card Slot | No |
| Flash Drive | No |
| Contains Battery | No |

Display Features

| | |
|----------------|-----------------|
| Analog/Digital | Analog |
| Display Size | 0.56" (14.2 mm) |
| Display Type | LED |
| Colors | Red or Green |

Certifications and Standards

| | |
|---------------------|------|
| Protection Class IP | IP65 |
| RoHS Compliant | Yes |
| CE | Yes |
| FCC | No |
| UKCA | Yes |
| UL | Yes |

PAX® Process Input Panel Meter, AC-Powered



Certifications and Standards

| | |
|---------------------|--|
| UL Information | E179259 |
| ATEX | No |
| DNV | No |
| KC | No |
| EMC | No |
| Environment | EN 61326-1 |
| Vibration and Shock | IEC 68-2-27: Operational 25 g (10 g relay); IEC 68-2-6: Operational 5 to 150 Hz, 2 g |