



Graphite® Rugged Indoor 12" HMI with dual Ethernet

Item number: G12C1100

The Graphite® Rugged Indoor 12" HMI with dual Ethernet connects, monitors and controls processes in any environment with the industry-leading touchscreen operator panel. These advanced HMIs offer protocol conversion, data logging, web-based monitoring and IEC 61131 programming control. Add I/O and functionality with expansion racks and plug-in modules.



All-aluminum construction featuring HMI panels and two Ethernet ports

Features and benefits

- ✓ **Easy to read screen**
Sleek, full-color, resistive analog touchscreen.
- ✓ **Rugged design for every environment**
Rugged, cast-aluminum housing is designed to operate reliably in harsh conditions and temperatures from -20° to 60°C. Built with high shock and vibration tolerance. Certified for hazardous locations.
- ✓ **Ethernet, serial and USB ports**
Devices come standard with 2 Ethernet ports, 2 RS-232 and 1 RS 485 serial ports, 1 USB device and 2 USB Host ports.
- ✓ **Email and SMS alerts**
Keep operators informed of machine and process performance with email or SMS notifications.
- ✓ **Crimson® Control programming**
Develop logic control easily. Simply add a plug-in Crimson Control module and leverage industry-standard IEC 61131 programming languages.
- ✓ **Compact and easy to install**
An HMI with a compact footprint for easy installation. Available as a 12 inch wide screen display.
- ✓ **Seamless connectivity for 300+ industrial drivers**
Unify multiple-vendor applications and network-enable equipment with drag and drop simplicity. Convert up to 20 protocols at once from a built-in library of over 300 supported drivers.
- ✓ **Built-in data logging and remote access**
An SD card provides built-in, continuous data logging and the visibility you need to support process improvements. In-built web and FTP servers provide remote monitoring and control capability.
- ✓ **Unparalleled expansion capabilities**
Choose from a wide range of field-installable plug-ins to seamlessly extend your capabilities. Modules include PID controllers, digital and analog I/O, RTD, and strain gage modules.

Graphite® Rugged Indoor 12" HMI with dual Ethernet



General	
Net Weight (g)	0.01
Packed Width (mm)	31.75
Packed Height (mm)	120.65
Packed Depth (mm)	63.5
Packed Weight (g)	2295.01
Operating Temperature °C Min	-20
Operating Temperature °C Max	60
Storage Temperature °C Min	-20
Storage Temperature °C Max	70
Relative Humidity	0 to 85% max. RH non-condensing
Power Consumption (W)	0
Input Voltage (V)	10-30 VDC
Maximum Installation Altitude (m)	2000
Mounting	Panel mount
Panel Cut-Out Dimensions	11.458" (291 mm) x 7.561" (192 mm)
Housing Materials	Aluminium
Front Sealing	Type 4X Indoor / IP66
Back Sealing	IP20
Packaging Material	Cardboard

Graphite® Rugged Indoor 12" HMI with dual Ethernet



General

Warranty (years)	2
------------------	---

Identification and Status

Product ID	G12C1100
Country of Origin	United States of America (the)
HS Code	8537109199
Dual Usage	No
Export Control Classification Number (ECCN)	EAR99

Physical Features

Connectors / Input / Output	Terminal, 2x RS232, 1x RS422/485, 2x RJ45, 1x USB Type B
SD Card Slot	Yes
Flash Drive	Yes
Contains Battery	No

Display Features

Display Size	12"
Display Type	Resistive analog
Pixels	1280 x 768
Colors	WXGA, 16M
Backlight Type	LED
Backlight Life Time (Typical)	70000 Hours
Backlight Brightness	400 cd/m2

Certifications and Standards

Protection Class IP	IP66
RoHS Compliant	Yes

Graphite® Rugged Indoor 12" HMI with dual Ethernet



Certifications and Standards	
CE	Yes
FCC	No
UKCA	Yes
UL	Yes
ATEX	Yes
DNV	No
KC	No
Vibration and Shock	IEC 68-2-27: Operational 40 g; IEC 68-2-6: Operational 5-500 Hz, 4 g