



## Graphite® Rugged Indoor 15" HMI

Item number: G15C0000

The Graphite® Rugged Indoor 15" HMI connects, monitors and controls processes in any environment with the industry-leading touchscreen operator panel. These advanced HMIs offer protocol conversion, data logging, web-based monitoring and IEC 61131 programming control. Add I/O and functionality with expansion racks and plug-in modules.



*All-aluminum construction featuring HMI panels*

### Features and benefits

- ✓ **Easy to read screen**  
Sleek, full-color, resistive analog touchscreen.
- ✓ **Rugged design for every environment**  
Rugged, cast-aluminum housing is designed to operate reliably in harsh conditions and temperatures from -20° to 60°C. Built with high shock and vibration tolerance. Certified for hazardous locations.
- ✓ **Ethernet, serial and USB ports**  
Devices come standard with 1 Ethernet port, 2 RS-232 and 1 RS 485 serial ports, 1 USB device and 2 USB Host ports.
- ✓ **Email and SMS alerts**  
Keep operators informed of machine and process performance with email or SMS notifications.
- ✓ **Crimson® Control programming**  
Develop logic control easily. Simply add a plug-in Crimson Control module and leverage industry-standard IEC 61131 programming languages.
- ✓ **Compact and easy to install**  
An HMI with a compact footprint for easy installation. Available as a 15 inch standard screen display.
- ✓ **Seamless connectivity for 300+ industrial drivers**  
Unify multiple-vendor applications and network-enable equipment with drag and drop simplicity. Convert up to 20 protocols at once from a built-in library of over 300 supported drivers.
- ✓ **Built-in data logging and remote access**  
An SD card provides built-in, continuous data logging and the visibility you need to support process improvements. In-built web and FTP servers provide remote monitoring and control capability.
- ✓ **Unparalleled expansion capabilities**  
Choose from a wide range of field-installable plug-ins to seamlessly extend your capabilities. Modules include PID controllers, digital and analog I/O, RTD, and strain gage modules.



# Graphite® Rugged Indoor 15" HMI

## General

Net Weight (g)	3500
Packed Width (mm)	31.75
Packed Height (mm)	120.65
Packed Depth (mm)	63.5
Packed Weight (g)	3515
Operating Temperature °C Min	-20
Operating Temperature °C Max	60
Storage Temperature °C Min	-20
Storage Temperature °C Max	70
Relative Humidity	0 to 85% relative humidity (non-condensing)
Power Consumption (W)	24
Input Voltage (V)	10 to 30 VDC
Maximum Installation Altitude (m)	2000
Mounting	Panel mount
Panel Cut-Out Dimensions	13.390" (340.1 mm) x 10.457" (265.6 mm)
Housing Materials	Aluminium
Front Sealing	Type 4X Indoor / IP66
Back Sealing	IP20
Packaging Material	Cardboard



# Graphite® Rugged Indoor 15" HMI

## General

Warranty (years)	2
------------------	---

## Identification and Status

Product ID	G15C0000
Country of Origin	United States of America (the)
HS Code	8537109199
Dual Usage	No
Export Control Classification Number (ECCN)	EAR99

## Physical Features

Connectors / Input / Output	Terminal, 2x RS232, 1x RS422/485, 1x RJ45, 1x USB Type B
SD Card Slot	Yes
Flash Drive	Yes
Contains Battery	No

## Display Features

Display Size	15"
Display Type	Resistive analog
Pixels	1024 x 768
Colors	XGA, 16M
Backlight Type	LED
Backlight Life Time (Typical)	70000 Hours
Backlight Brightness	400 cd/m2

## Certifications and Standards

Protection Class IP	IP66
RoHS Compliant	Yes



# Graphite® Rugged Indoor 15" HMI

## Certifications and Standards

<b>CE</b>	Yes
<b>FCC</b>	No
<b>UKCA</b>	Yes
<b>UL</b>	Yes
<b>UL Information</b>	E302106
<b>ATEX</b>	Yes
<b>ATEX Information</b>	II 3 G Ex ic nA IIC T4 Gc II 3 D Ex tc IIIC T135°C Dc DEMKO 14 ATEX 1387X EN 60079-0, -11, -15, -31 UL23UKEX2879X
<b>DNV</b>	No
<b>KC</b>	No
<b>EMC</b>	No
<b>Environment</b>	EN 61326-1, EN 61010-1