



1/16 DIN, AC Power, 0 to 10 VDC, Relay, CT and 1 User Input, RS-485 PID Controller

Item number: PXU41B20

The PXU 1/16 DIN, AC Power, 0 to 10 VDC, CT and 1 User Input, RS-485 PID Controller is simple to program with a large, easy to read display that's easy to mount in small areas. Dependable operation in industrial environments. Give your operation full confidence with industry-leading PID control for a range of applications.



A PID controller for basic needs with universal input capability

Features and benefits

✓ PID control you can count on

Reliable PID control for a range of basic to advanced requirements. Suitable for simple on/off applications or for scenarios requiring full PID control.

✓ Main Control

0 to 10 VDC

✓ Control Input

CT Input

✓ Protected dual line display for easy readability

Dual line display with 4 digits on each line. Large enough for operators to read at a distance. Front panel is dust-proof with IP65 protection.

✓ Simple programming with Crimson® configuration software

Program multiple units easily with Crimson. No-nonsense configuration is fast and simple through checkboxes and numerical entries.

✓ Runs on AC power

100 to 240 VAC

✓ Compact packaging

Economize space with 1/16 DIN packaging designed for areas with reduced depth.

✓ Secondary Control

Relay

✓ RS-485 connectivity

Use the RS-485 port to collect process values and display data remotely. Simple setup with Crimson configuration software.

✓ Universal input capability

Get input and display data easily from pressure transducers, flow meters, current transducers, RTDs and thermocouples. Select input with front panel push buttons or using Crimson configuration software.

✓ Performance indicators and alerts

Extend performance visibility by enabling status indicators. Configurable for alarm requirements, control features and temperature.

1/16 DIN, AC Power, 0 to 10 VDC, Relay, CT and 1 User Input, RS-485 PID Controller



General

Net Weight (g)	150.25235
Packed Weight (g)	150.25235
Operating Temperature °C Min	0
Operating Temperature °C Max	50
Storage Temperature °C Min	-20
Storage Temperature °C Max	65
Relative Humidity	80% max relative humidity (non-condensing) from 0 °C to 50 °C
Power Consumption (W)	8
Input Voltage (V)	100 to 240 VAC
Maximum Installation Altitude (m)	2000
Mounting	Panel mount
Panel Cut-Out Dimensions	1.77" (45 mm) x 1.77" (45 mm)
Housing Materials	Plastic
Front Sealing	IP65 requirements for indoor use
Packaging Material	Cardboard
Warranty (years)	2

Identification and Status

Product ID	PXU41B20
Country of Origin	Taiwan (Province of China)
HS Code	9032890090

1/16 DIN, AC Power, 0 to 10 VDC, Relay, CT and 1 User Input, RS-485 PID Controller



Identification and Status

Dual Usage	No
------------	----

Physical Features

Connectors / Input / Output	Terminal, 1x RS485
-----------------------------	--------------------

SD Card Slot	No
--------------	----

Flash Drive	No
-------------	----

Contains Battery	No
------------------	----

Display Features

Display Size	Line 1 - 0.43" (11 mm); Line 2 - 0.270" (7.0 mm)
--------------	--

Display Type	LCD
--------------	-----

Backlight Type	Orange and Green
----------------	------------------

Certifications and Standards

Protection Class IP	IP65
---------------------	------

RoHS Compliant	Yes
----------------	-----

CE	Yes
----	-----

FCC	No
-----	----

UKCA	Yes
------	-----

UL	Yes
----	-----

ATEX	No
------	----

DNV	No
-----	----

KC	No
----	----

Vibration and Shock	Shock: Operational 30 g; Vibration: Operational 10 to 55 Hz, 1 g
---------------------	--