RedLing[®] 1/8 DIN, DC Power, Relay Output PID Controller

Item number: PXU100C0

The PXU 1/8 DIN, DC Power, Relay Output PID Controller is simple to program with a large, easy to read display that's easy to mount in small areas. Dependable operation in industrial environments. Give your operation full confidence with industry-leading PID control for a range of applications.

Features and benefits

PID control you can count on

Reliable PID control for a range of basic to advanced requirements. Suitable for simple on/off applications or for scenarios requiring full PID control.



Relay Output

Universal input capability

Get input and display data easily from pressure transducers, flow meters, current transducers, RTDs and thermocouples. Select input with front panel push buttons or using Crimson configuration software.



Performance indicators and alerts

Extend performance visibility by enabling status indicators. Configurable for alarm requirements, control features and temperature.



A PID controller for basic needs with universal input capability

Compact packaging

Economize space with 1/8 DIN packaging designed for areas with reduced depth.

Protected dual line display for easy readability

Dual line display with 4 digits on each line. Large enough for operators to read at a distance. Front panel is dust-proof with IP65 protection.

Simple programming with Crimson[®] configuration software

Program multiple units easily with Crimson. No-nonsense configuration is fast and simple through checkboxes and numerical entries.

Runs on DC power

24 V



1/8 DIN, DC Power, Relay Output PID Controller



General	
Net Weight (g)	454
Packed Weight (g)	454
Operating Temperature °C Min	0
Operating Temperature °C Max	50
Storage Temperature °C Min	-20
Storage Temperature °C Max	65
Relative Humidity	80% max relative humidity (non-condensing) from 0 °C to 50 °C
Power Consumption (W)	8
Input Voltage (V)	24 VDC
Maximum Installation Altitude (m)	2000
Mounting	Panel mount
Panel Cut-Out Dimensions	1.76" (44.5 mm) x 3.6" (91.5 mm)
Housing Materials	Plastic
Front Sealing	IP65
Packaging Material	Cardboard
Warranty (years)	2

Identification and Status

Product ID	PXU100C0
Country of Origin	Taiwan (Province of China)
HS Code	9032890090



1/8 DIN, DC Power, Relay Output PID Controller



Identification and Status	
Dual Usage	No
Physical Features	
Connectors / Input / Output	Terminal
SD Card Slot	No
Flash Drive	No
Contains Battery	No
Display Features	
Analog/Digital	Digital
Display Size	Line 1 - 0.47" (12 mm); Line 2 - 0.47" (12 mm)
Display Type	LCD
Backlight Type	Orange and Green
Certifications and Standards	
Protection Class IP	IP65
RoHS Compliant	Yes
CE	Yes
FCC	No
UKCA	Yes
UL	Yes
ATEX	No
DNV	No
КС	No
Vibration and Shock	Shock: Operational 30 g; Vibration: Operational 10 to 55 Hz, 1 g

