

# Large 4" 6-digit LED Counter Display

Item number: LD400600

The Large 4" 6-digit LED Counter Display helps you visualize real-time operations data. Display up to 6 digits at 4" (101 mm) in height. Furnish your industrial application with reliable visual display performance that's durable and easy to program. Network display values using optional serial communication ports.



Reliable, rugged and versatile display to visualize your data from a distance

### Features and benefits

Readable at a distance

Large display and digits make values readable from distances up to 180 feet for easy monitoring.

Large, 6-digit display

Display up to 6 digits measuring 4" (101 mm) in height.

Sealed enclosure with NEMA 4X and IP65 protection

Air-tight and water-tight casing and pressure vent for rapid temperature swings makes the display perfect for industrial applications.

Accept and visualize counter input

Collect accurate count in real time for measurement, monitoring and reporting.

Universal AC/DC power

Power input range from 50 to 250VAC / 21.6 to 250VDC.

✓ Variable brightness

Red LED lights have adjustable intensity.

Rugged casing

Packaged in lightweight aluminum housing for durability in industrial environments. Dimensions: 660 x 200 x 58mm

Easy programming using push buttons or a PC

Program the device directly or from a PC using Crimson® configuration software. Set and adjust signal and user inputs, scaling and other parameters.

Dual setpoint control for alert capability

Alarm setpoints let operators easily see when counter limits are being approached or exceeded.







General	
Net Weight (g)	4756.5
Packed Weight (g)	4756.5
Operating Temperature °C Min	0
Operating Temperature °C Max	65
Storage Temperature °C Min	-40
Storage Temperature °C Max	70
Relative Humidity	0 to 85% max. RH (non-condensing)
Power Consumption (W)	11
Input Voltage (V)	21.6 to 250 VDC
Maximum Installation Altitude (m)	2000
Mounting	Wall mount
Housing Materials	Aluminium
Front Sealing	Type 4X Indoor/Outside / IP65
Packaging Material	Cardboard
Warranty (years)	2

#### 







UN/CICAI	LEGATURGE
	Features
1 11,01041	i oatai oo

Connectors / Input / Output	Terminal
SD Card Slot	No
Flash Drive	No
Contains Battery	No

## Display Features

Display Size	4" (101 mm)
Colors	Red

## Certifications and Standards

Protection Class IP	IP65
RoHS Compliant	Yes
CE	Yes
FCC	No
UKCA	No
UL	Yes
ATEX	No
DNV	No
КС	No
Vibration and Shock	Shock: IEC 68-2-27: Operational 30 g; Vibration: IEC 68-2-6: Operational 5 to 150 Hz, 2 g

