



1/16 DIN, AC Power, 4 to 20 mA, Relay, Remote Setpoint and 1 User Input, RS-485 PID Controller

Item number: PXU31D20

The PXU 1/16 DIN, AC Power, 4 to 20 mA, Remote Setpoint and 1 User Input, RS-485 PID Controller is simple to program with a large, easy to read display that's easy to mount in small areas. Dependable operation in industrial environments. Give your operation full confidence with industry-leading PID control for a range of applications.



A PID controller for basic needs with universal input capability

Features and benefits

- ✓ **PID control you can count on**
Reliable PID control for a range of basic to advanced requirements. Suitable for simple on/off applications or for scenarios requiring full PID control.
- ✓ **Main Control**
4 to 20 mA
- ✓ **Control Input**
Remote Setpoint
- ✓ **Protected dual line display for easy readability**
Dual line display with 4 digits on each line. Large enough for operators to read at a distance. Front panel is dust-proof with IP65 protection.
- ✓ **Simple programming with Crimson® configuration software**
Program multiple units easily with Crimson. No-nonsense configuration is fast and simple through checkboxes and numerical entries.
- ✓ **Runs on AC power**
100 to 240 VAC
- ✓ **Compact packaging**
Economize space with 1/16 DIN packaging designed for areas with reduced depth.
- ✓ **Secondary Control**
Relay
- ✓ **RS-485 connectivity**
Use the RS-485 port to collect process values and display data remotely. Simple setup with Crimson configuration software.
- ✓ **Universal input capability**
Get input and display data easily from pressure transducers, flow meters, current transducers, RTDs and thermocouples. Select input with front panel push buttons or using Crimson configuration software.
- ✓ **Performance indicators and alerts**
Extend performance visibility by enabling status indicators. Configurable for alarm requirements, control features and temperature.

1/16 DIN, AC Power, 4 to 20 mA, Relay, Remote Setpoint and 1 User Input, RS-485 PID Controller



General

Net Weight (g)	150.25235
Packed Weight (g)	150.25235
Operating Temperature °C Min	0
Operating Temperature °C Max	50
Storage Temperature °C Min	-20
Storage Temperature °C Max	65
Relative Humidity	80% max relative humidity (non-condensing) from 0 °C to 50 °C
Power Consumption (W)	8
Input Voltage (V)	100 to 240 VAC
Maximum Installation Altitude (m)	2000
Mounting	Panel mount
Panel Cut-Out Dimensions	1.77" (45 mm) x 1.77" (45 mm)
Housing Materials	Plastic
Front Sealing	IP65 requirements for indoor use
Packaging Material	Cardboard
Warranty (years)	2

Identification and Status

Product ID	PXU31D20
Country of Origin	Taiwan (Province of China)
HS Code	9032890090

1/16 DIN, AC Power, 4 to 20 mA, Relay, Remote Setpoint and 1 User Input, RS-485 PID Controller



Identification and Status

Dual Usage	No
------------	----

Physical Features

Connectors / Input / Output	Terminal, 1x RS485
-----------------------------	--------------------

SD Card Slot	No
--------------	----

Flash Drive	No
-------------	----

Contains Battery	No
------------------	----

Display Features

Display Size	Line 1 - 0.43" (11 mm); Line 2 - 0.270" (7.0 mm)
--------------	--

Display Type	LCD
--------------	-----

Backlight Type	Orange and Green
----------------	------------------

Certifications and Standards

Protection Class IP	IP65
---------------------	------

RoHS Compliant	Yes
----------------	-----

CE	Yes
----	-----

FCC	No
-----	----

UKCA	Yes
------	-----

UL	Yes
----	-----

ATEX	No
------	----

DNV	No
-----	----

KC	No
----	----

Vibration and Shock	Shock: Operational 30 g; Vibration: Operational 10 to 55 Hz, 1 g
---------------------	--