



CUB®5 Miniature DC Current Panel Meter with Reflective Display

Item number: CUB5IR00

The CUB®5 Miniature DC Current Panel Meter with Reflective Display is compact and powerful to help you stay on top of industrial measurements. Simple to install and easy to read. Designed with flexibility in mind. Simply upgrade your meter with field-installable option cards when you need new communication and setpoint capability.



A compact and reliable panel meter that evolves as your needs change

Features and benefits

✓ **Compact and durable design**

The miniature size is designed to fit any industrial setting or application, measuring: width 2.68" (68 mm) x height 1.3" (33 mm) x depth 1.29" (44 mm).

✓ **Large easy-to-read display**

See counts and measurements easily on a 0.48" (12 mm) 5-digit reflective display.

✓ **Optional communications and programming cards**

Add communications capability with optional cards. Choose from RS232 and RS485. For Crimson® programming, add a USB programming card.

✓ **Wide power input**

Powered by 9 to 28 VDC. AC power available with optional module.

✓ **Field proven and time tested**

Decades of proven reliability and recognized across industries as a leader in panel meters

✓ **Programming ease and flexibility**

Set up and adjust with the press of a few buttons or using Crimson® software simply click through the capabilities you want to enable and disable.

✓ **Field-installable output cards**

When applications or requirements change, upgrade your meter instead of replacing it. Plug-and-play option cards enable new communications and setpoints.

✓ **Optional setpoint cards**

Add setpoint capability with optional cards. Choose from single relay or dual sinking.

✓ **Reliable analog measurement**

Whatever parameter you need to monitor, the CUB® series covers it. Keep track of current.

CUB®5 Miniature DC Current Panel Meter with Reflective Display



General	
Net Weight (g)	0.2
Packed Weight (g)	0.2
Operating Temperature °C Min	-35
Operating Temperature °C Max	75
Storage Temperature °C Min	-35
Storage Temperature °C Max	85
Relative Humidity	0 to 85% relative humidity (non-condensing)
Power Consumption (W)	0
Input Voltage (V)	9-28 VDC
Maximum Installation Altitude (m)	2000
Mounting	Panel mount
Panel Cut-Out Dimensions	2.62" (66.6 mm) x 1.29" (32.8 mm)
Housing Materials	Plastic
Front Sealing	Type 4X/IP65
Back Sealing	IP20
Packaging Material	Cardboard
Warranty (years)	2
Identification and Status	
Product ID	CUB5IR00
Country of Origin	United States of America (the)

CUB®5 Miniature DC Current Panel Meter with Reflective Display



Identification and Status

HS Code	9030337000
Dual Usage	No

Physical Features

Connectors / Input / Output	Terminal block, 1x RS232 or RS485
SD Card Slot	No
Flash Drive	No
Contains Battery	No

Display Features

Analog/Digital	Digital
Display Type	Reflective

Certifications and Standards

Protection Class IP	IP65
RoHS Compliant	Yes
CE	Yes
FCC	No
UKCA	Yes
UL	Yes
ATEX	No
DNV	No
KC	No
Vibration and Shock	IEC 68-2-27: Operational 30 g; IEC 68-2-6: Operational 5-500 Hz, 5 g