



PAX® Dual Counter, DC-Powered

Item number: PAXC0030

The DC-Powered PAX® Dual Counter helps you visualize analog and digital inputs with reliable panel meters that save you money and reduce downtime. When requirements change, simply upgrade your meter with field-installable, plug-and-play option cards to add communication, programming, I/O and setpoint capability.



Visualize and control industrial processes with a field-upgradable panel meter

Features and benefits

✓ **Recognized as an industrial standard**

For 23 years, the PAX Meter has been voted North America's number 1 panel meter by Control Design's readers.

✓ **Compact, easy to read display**

Visualize critical performance data easily on a 6-digit 0.56" (14 mm) red sunlight readable LED display.

✓ **Field-upgradable communications and programming cards**

Add communications or programming capability with optional cards. Choose from RS232, RS485, Modbus®, PROFIBUS-DP and Crimson® programming.

✓ **Field-upgradable setpoint cards**

Add setpoint capability with optional cards. Choose from dual relay, quad relay, quad sinking and quad sourcing.

✓ **Agency Approved**

UL listed

✓ **Visualize any digital parameter**

Whatever parameter you need to monitor, the PAX series covers it. Keep track of count.

✓ **Customizable units for evolving demands**

When needs change, upgrade your meter instead of replacing it. Plug-and-play option cards add new capabilities. Choose from programming, communications, analog output and setpoints cards.

✓ **Field-upgradable analog output cards**

Install a single analog output card for 0 to 20 mA, 4 to 20 mA or 0 to 10 VDC

✓ **Runs on DC power.**

Uses 11-36 DC.

PAX® Dual Counter, DC-Powered



General

Net Weight (g)	0.6313
Packed Weight (g)	0.6313
Operating Temperature °C Min	0
Operating Temperature °C Max	50
Storage Temperature °C Min	-40
Storage Temperature °C Max	60
Relative Humidity	0 to 85% max. RH non-condensing
Input Voltage (V)	11 to 36 VDC
Maximum Installation Altitude (m)	2000
Mounting	Panel mount
Panel Cut-Out Dimensions	3.62" (92 mm) x 1.77" (45 mm)
Housing Materials	Polycarbonate
Front Sealing	NEMA 4X/IP65 outdoor
Back Sealing	IP20
Packaging Material	Cardboard
Warranty (years)	2

Identification and Status

Product ID	PAXC0030
Country of Origin	United States of America (the)
HS Code	9029100090

PAX® Dual Counter, DC-Powered



Identification and Status

Dual Usage	No
------------	----

Physical Features

Connectors / Input / Output	Terminal
-----------------------------	----------

SD Card Slot	No
--------------	----

Flash Drive	No
-------------	----

Contains Battery	No
------------------	----

Display Features

Analog/Digital	Analog
----------------	--------

Display Size	0.56" (14.2 mm)
--------------	-----------------

Display Type	LED
--------------	-----

Colors	Red or Green
--------	--------------

Certifications and Standards

Protection Class IP	IP65
---------------------	------

RoHS Compliant	Yes
----------------	-----

CE	Yes
----	-----

FCC	No
-----	----

UKCA	Yes
------	-----

UL	Yes
----	-----

ATEX	No
------	----

DNV	No
-----	----

KC	No
----	----

Vibration and Shock	IEC 68-2-27: Operational 25 g (10 g relay); IEC 68-2-6: Operational 5 to 150 Hz, 2 g
---------------------	--