



Phone Modem with RS-232, RS-422 and RS-485 Ports

Item number: VT-MODEM-3WW

The VT-MODEM-3WW Phone Modem with RS-232, RS-422 and RS-485 Ports is a durable modem which delivers high performing phone and fax capability in extreme indoor and outdoor industrial settings. 10-52 VDC power input eliminates the need for AC adapters. Supports all devices, complies with telephone systems worldwide, and rated for -30° to +70°C.



Features and benefits



Phone Modem with RS-232, RS-422 and RS-485 Ports



| General | |
|------------------------------|-----------------------------------|
| Net Weight (g) | 453.592 |
| Packed Weight (g) | 453.592 |
| Operating Temperature °C Min | -30 |
| Operating Temperature °C Max | 70 |
| Storage Temperature °C Min | -40 |
| Storage Temperature °C Max | 85 |
| Relative Humidity | 5% to 95% (non condensing) |
| Power Consumption (W) | 0 |
| Input Voltage (V) | 10-30 VDC |
| Mounting | DIN rail mount (bracket included) |
| Packaging Material | Cardboard |
| Warranty (years) | 2 |
| Identification and Status | |
| Product ID | VT-MODEM-3WW |
| Country of Origin | Taiwan (Province of China) |
| HS Code | 8517620000 |
| Dual Usage | No |
| Physical Features | |
| SD Card Slot | No |
| Flash Drive | No |
| Contains Battery | No |

Phone Modem with RS-232, RS-422 and RS-485 Ports



| Certifications and Standards | |
|------------------------------|-------------------------|
| RoHS Compliant | No |
| CE | No |
| FCC | Yes |
| UKCA | No |
| UL | Yes |
| ATEX | Yes |
| DNV | No |
| KC | No |
| Vibration and Shock | Vibration: IEC60068-2-6 |