



N-Tron® 1000-POE4+ Gigabit Midspan Injector

Item number: 1000-POE4+

The N-Tron 8-port PoE Gigabit Injector simplifies network device deployment with this unmanaged plug-and-play injector. Eight ports in total, with four 10/100/1000BaseT(X) RJ45 ports and four auto-sensing PoE+ ports for reliable data and power transfer. Performance, durability and ease of use for bandwidth intensive network needs in rugged environments.



8-port PoE injector offers Gigabit data and power transfer over a single cable

Features and benefits

- ✓ **High-speed, high performance data transmission**
Full wire speed communication and high throughput (up to 8.0 Gb/s) for high bandwidth applications.
- ✓ **8 total ports for flexibility**
Four 10/100/1000BaseT(X) RJ-45 ports (data in) and four 10/100/1000BaseT(X) RJ-45 PoE+ ports (data and power out).
- ✓ **Engineered for industrial settings**
Full IEEE 802.3 af/at compliance. Suitable for hazardous environments with UL Class I, Division 2 listing and CE and CSA certifications. ABS Type approval for shipboard applications. Operating temperature of -40 °C to 85 °C and over 2 million hours MTBF.
- ✓ **Redundant power inputs**
Redundant DC power inputs (22-49 VDC) offer increased reliability and stay running in case of power supply failure.
- ✓ **Save time and money with Power over Ethernet (PoE)**
Power any PoE-capable camera or wireless access point. Auto-senses PoE devices. Delivers 30 Watts output (25.5 Watts at PD).
- ✓ **Compact, rugged metal case**
Designed with a hardened metal, DIN-rail mountable case. Compact design for easy installation in tight spaces. Dimensions: 5.9" X 2.0" X 5.9".
- ✓ **LED status monitoring**
LED indicator lights display PoE connectivity and power fault status.



N-Tron® 1000-POE4+ Gigabit Midspan Injector

General

Net Weight (g)	656.85
Packed Weight (g)	656.85
Operating Temperature °C Min	-40
Operating Temperature °C Max	80
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Relative Humidity	10% to 95% (Non Condensing)
Maximum Installation Altitude (m)	3048
Packaging Material	Cardboard
Warranty (years)	3

Identification and Status

Product ID	1000-POE4+
Country of Origin	United States of America (the)
HS Code	8517620000
Dual Usage	No

Physical Features

Top Wiring Clearance (mm)	25.4
Front Wiring Clearance (mm)	50.8
SD Card Slot	No
Flash Drive	No
Contains Battery	No



N-Tron® 1000-POE4+ Gigabit Midspan Injector

Certifications and Standards

RoHS Compliant	Yes
CE	No
FCC	No
UKCA	No
UL	No
ATEX	No
DNV	No
KC	No
Mean Time Before Failure (MTBF)	>2 million
Vibration and Shock	Shock: 200 g @ 10 ms ; Vibration: 50 g, 5-200 Hz, triaxial