



Anybus CompactCom Connector Board - CANopen

Item number: AB6667-B

Used together with the CompactCom Brick to get quick and easy access to network connectors.



Network connectors - ready for use together with the CompactCom Brick

Features and benefits

✓ **Easy mounting**

Incorporates a male strip connector - pluggable and solderable.

✓ **Modular**

Mix and match CompactCom Bricks and connector boards to give your host application access to different networks.

✓ **Robust**

Safe and secure mounting of the brick interface to the host PCB design.

✓ **Compatible with Starter Kit**

Used together with the Anybus CompactCom Starter Kit (Brick version) to get access to the right network connectors.

Anybus CompactCom Connector Board - CANopen



General

Net Width (mm)	40
Net Height (mm)	16
Net Depth (mm)	39
Net Weight (g)	10
Packed Weight (g)	10
Operating Temperature °C Min	-40
Operating Temperature °C Max	85
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Isolation	Galvanic Isolation
Content of Delivery	Connector board
Not Included (in delivery)	Female strip connector, stand-off spacer
Mounting	PCB mounting via a customized CompactFlash connector
Warranty (years)	1 year

Identification and Status

Product ID	AB6667-B
Country of Origin	Sweden
HS Code	8517620000
Dual Usage	No

Physical Features

Connectors / Input / Output	1x 9-pin D-SUB male
-----------------------------	---------------------

Anybus CompactCom Connector Board - CANopen



Physical Features

Contains Battery	No
------------------	----



Use Case

