

## Anybus Communicator EtherNet/IP Scanner - PROFIBUS DP Device ATEX

Item number: ABC3300EX-A

The Anybus Communicator EtherNet/IP Scanner to PROFIBUS ATEX enables you to connect EtherNet/IP devices to PROFIBUS control systems. Anybus Communicators ensure reliable, secure, and high-speed data transfer between different industrial networks. Thanks to our intuitive web-based user interface, they're also incredibly easy to use.



*A protocol converter that connects EtherNet/IP devices to PROFIBUS control systems*

### Features and benefits

- ✓ **Connect 32 adapters with EDS import**  
Supports up to 32 adapters, 500 bytes per connection (Class 1 Exclusive Owner), and an RPI down to 1 ms for demanding applications. Import EDS files via the web interface for easy mapping or configure connections manually.
- ✓ **EX certified**  
Certified for ATEX Zone 2 and UL Hazardous Location Class 1 Division 2 for use in areas where explosive gas may exist.
- ✓ **Configure via web interface over Ethernet**  
With a graphical and responsive web interface, configuration is a breeze. In addition, there's no software to install and the dedicated Ethernet configuration port makes it easy to get started.
- ✓ **Drop-in replacement**  
Already using an X-gateway? Don't worry, with legacy mode you can continue using the same configuration in your controller/PLC.
- ✓ **Built for factory floors**  
The Gateway is made with industrial-grade components, verified to meet industry standards, and backed by a 5-year warranty. Its slim form factor, front-facing ports, and cable tie make DIN-rail installation easy.
- ✓ **Transfer 244 bytes to and from PROFIBUS controller (PLC)**  
Transfer up to 244 bytes in each direction (488 bytes total). PROFIBUS DP device (slave) with automatic baud rate detection. Address setting via rotary switches or web interface. Includes a GSD file.
- ✓ **Instant data transfer**  
The Communicator transfers data instantly between networks, with processing time so low you don't even need to count it, as it's in line with network jitter. Just add the cycle times of both networks to get the total transfer time.
- ✓ **Diagnostics and support**  
The user interface shows connection status, allowing you to monitor data going through the gateway. Monitor and control nodes via the Live List and Data Exchange Control features. Our global support team is ready to help if needed.
- ✓ **Secure and segment networks**  
Secure boot blocks malware, while a security switch locks configurations to prevent unauthorized changes. Network segmentation is inherent in the design, as each network is run separately, with only configured data transferred between networks.

# Anybus Communicator EtherNet/IP Scanner - PROFIBUS DP Device ATEX



General	
Net Weight (g)	150
Packed Width (mm)	35
Packed Height (mm)	170
Packed Depth (mm)	115
Packed Weight (g)	150
Operating Temperature °C Min	-25
Operating Temperature °C Max	70
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Type Value at Vcc Nom (mA)	90mA @ 24V DC (2.2W)
Current Consumption Max value at Vcc nom (mA)	125mA @24V DC (3W)
Input Voltage (V)	12-30V DC
Power Connector	3-pin, 5.08 Phoenix plug connector
Reverse Polarity Protection	Yes
Short Circuit Protection	Yes
Isolation	Yes
Mounting	DIN-rail (EN 50022 standard)
Housing Materials	PC ABS, UL 94 VO
Packaging Material	Cardboard

# Anybus Communicator EtherNet/IP Scanner - PROFIBUS DP Device ATEX



## Identification and Status

Product ID	ABC3300EX-A
Model Code	40-ETH-PDP-A-EX
Predecessor	AB7671-F
Country of Origin	Sweden
HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN)	5A991.b.1

## Physical Features

Connectors / Input / Output	2xRJ45;1x D-sub 9-pin female PROFIBUS connector;RJ45 Config port
Push Buttons	Factory reset
DIP & Rotary Switches	Security lock switch
Contains Battery	No

## EtherNet/IP Features

EtherNet/IP Mode	Scanner / Master
EtherNet/IP Supported Functionality	EDS import; Endian conversion (byte swap); LiveList; DataExchangeControl; QoS; CT20 ODVA Conformance
EtherNet/IP No. Of Adapters	32
EtherNet/IP Configuration File	EDS available
EtherNet/IP Bandwidth	10/100 MBit down to 1ms cycle time
EtherNet/IP Input Data Size	1500 bytes
EtherNet/IP Output Data Size	1500 bytes

## PROFIBUS Features

PROFIBUS Mode	DP Device
---------------	-----------

# Anybus Communicator EtherNet/IP Scanner - PROFIBUS DP Device ATEX



## PROFIBUS Features

<b>PROFIBUS Supported Functionality</b>	PROFIBUS-DP Slave functionality according to extensions of EN 50170
<b>PROFIBUS Device Address</b>	0-125
<b>PROFIBUS Configuration File</b>	GSD available
<b>PROFIBUS Baud Rate</b>	9600 bit/s - 12 Mbit/s
<b>PROFIBUS Input Data Size</b>	244 bytes
<b>PROFIBUS Output Data Size</b>	244 bytes

## Certifications and Standards

<b>Protection Class IP</b>	IP20
<b>RoHS Compliant</b>	Yes
<b>Recycle / Disposal</b>	Yes
<b>CE</b>	Yes
<b>FCC</b>	No
<b>UL</b>	Yes
<b>UL Information</b>	E214107: Ord.Loc UL 61010-1, CSA C22.2 No. 61010-1, UL 61010-2-201, CSA C22.2 No. 61010-2-201; E203225: Haz.Loc CL I DIV2 GP A,B,C,D T4, UL 121201, CAN/CSA C22.2 NO. 213-17
<b>ATEX</b>	Yes
<b>ATEX Information</b>	II 3 G Ex ec IIC T4 Gc, EN IEC 60079-0, 60079-7, IEC 60664-1
<b>KC</b>	Yes
<b>EMC</b>	Yes
<b>Environment</b>	EN 55016-2-3 Class A, EN 55032 Class A, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6
<b>Waste Certification (WEEE)</b>	Yes