

Anybus CompactCom 30 Module RS-485/422 without housing

Item number: AB6308-B

The Anybus CompactCom 30 RS-485/422 without housing is a passive module that acts as a physical layer converter for RS-485/422 communication. As a passive module, it doesn't process the serial bitstream. This module enables a transparent RS-485/422 channel using the Anybus CompactCom slot. The module uses the serial channel of the application interface.



Enables transparent RS-485/422 communication

Features and benefits

Anybus CompactCom 30 Module RS-485/422 without housing



General

Net Width (mm)	37
Net Height (mm)	16
Net Depth (mm)	51
Net Weight (g)	18
Packed Weight (g)	18
Operating Temperature °C Min	-40
Operating Temperature °C Max	85
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Class (CompactCom series)	A
Input Voltage (V)	3.3 VDC, +/- 0.15 VDC
Application Interface	RxD/TxD
Isolation	Galvanic Isolation
Content of Delivery	CompactCom M30 Passive module
Mounting	PCB mounting via a customized CompactFlash connector
Warranty (years)	1

Identification and Status

Product ID	AB6308-B
Country of Origin	Sweden
HS Code	8517620000

Anybus CompactCom 30 Module RS-485/422 without housing



Identification and Status

Dual Usage	No
------------	----

Physical Features

Connectors / Input / Output	D-sub
LED Indicators	Power
Form Factor	Module without Housing
Contains Battery	No

Certifications and Standards

Protection Class IP	IP20
RoHS Compliant	Yes
Product Certifications	RoHS, UL
UL Information	E214107