

Anybus CompactCom 30 Module RS-232

Item number: AB6207-B

The Anybus CompactCom 30 RS-232 is a passive module that acts as a physical layer converter for RS-232 communication. As a passive module, it doesn't process the serial bitstream. This module enables a transparent RS-232 channel using the Anybus CompactCom slot. The module uses the serial channel of the application interface.



Enables transparent RS-232 communication

Features and benefits



General

Net Width (mm)	50
Net Height (mm)	22
Net Depth (mm)	52
Net Weight (g)	26
Packed Weight (g)	26
Operating Temperature °C Min	-40
Operating Temperature °C Max	70
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Class (CompactCom series)	A
Input Voltage (V)	3.3 VDC, +/- 0.15 VDC
Application Interface	RxD/TxD
Isolation	Galvanic Isolation
Content of Delivery	CompactCom M30 Passive module
Mounting	PCB mounting via a customized CompactFlash connector
Warranty (years)	1

Identification and Status

Product ID	AB6207-B
Country of Origin	Sweden
HS Code	8517620000



Identification and Status

Dual Usage	No
------------	----

Physical Features

Connectors / Input / Output	Network: D-sub Male, Host: 50 pin Compact Flash connector
LED Indicators	Power
Form Factor	Module
Contains Battery	No

Certifications and Standards

Protection Class IP	IP20
RoHS Compliant	Yes
Product Certifications	RoHS, UL
UL Information	E214107