



Anybus Communicator – Serial Master to PROFINET IO

Item number: AB7013-C

The Anybus Communicator – Serial Master to PROFINET IO converts serial protocols to PROFINET IO, enabling you to connect any RS-232/485 device or equipment to PROFINET IO control systems. Anybus Communicators ensure reliable, secure, high-speed data transfers between different industrial networks while being easy to use.



A protocol converter that connects serial devices to PROFINET IO control systems.

Features and benefits

Anybus Communicator – Serial Master to PROFINET IO



General

Net Width (mm)	27
Net Height (mm)	120
Net Depth (mm)	75
Net Weight (g)	150
Packed Width (mm)	135
Packed Height (mm)	55
Packed Depth (mm)	170
Packed Weight (g)	300
Operating Temperature °C Min	0
Operating Temperature °C Max	55
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Relative Humidity	0-95% non condensing
Current Consumption Type Value at Vcc Nom (mA)	100mA @ 24V DC
Current Consumption Max value at Vcc nom (mA)	300mA @ 24V DC
Input Voltage (V)	24V DC (-10% to +10%)
Power Connector	2-pin, 5.08 Phoenix plug connector
Reverse Polarity Protection	Yes
Short Circuit Protection	Yes

Anybus Communicator – Serial Master to PROFINET IO



General

Isolation	TRUE
Maximum Installation Altitude (m)	up to 2 000 m
Mounting	DIN-rail (EN 50022 standard)
Housing Materials	PC ABS, UL 94
Packaging Material	Cardboard

Identification and Status

Product ID	AB7013-C
Successor	ABC3013-A
Country of Origin	Sweden
HS Code	8517620000
Dual Usage	No

Physical Features

Connectors / Input / Output	1x D-sub 9-pin female, 2x RJ45
Contains Battery	No

Modbus-RTU Features

Modbus-RTU Mode	Client / Master
Modbus-RTU Supported Functionality	RS-232; RS-422; RS-485; DF1; Standard Modbus RTU Master; Custom Request / Response commands; Custom Produce / Consume transactions; Trigger initiated transactions 7 or 8 data bit; None, Odd, Even Parity; 1 or 2 stop bit; Clear/Freeze
Modbus-RTU Functions Supported	1, 2, 3, 4, 5, 6, 7, 8, 11, 12, 15, 16, 17, 20, 21, 22, 24
Modbus-RTU Baud Rate	1200,1800,2400,4800,7200,9600,14400,19200,35700,38400,57600 bit/s
Modbus-RTU Input Data Size	512 bytes
Modbus-RTU Output Data Size	512 bytes

PROFINET Features

PROFINET Mode	Slave
---------------	-------

Anybus Communicator – Serial Master to PROFINET IO



PROFINET Features

PROFINET Supported Functionality	Soft Real-Time (RT); Max 64 slots / 1 sub-slot; DCP support; Acyclic Data exchange
PROFINET Configuration File	GSDML available
PROFINET Bandwidth	10/100Mbit full/half duplex down to 1ms
PROFINET Input Data Size	512 bytes
PROFINET Output Data Size	512 bytes

Serial Features

Connector	1x D-sub 9-pin female
Max Nodes	31
Baud Rate	1200,1800,2400,4800,7200,9600,14400,19200,35700,38400,57600 bit/s
Supported Functionality	RS-232; RS-422; RS485; DF1; Standard Modbus RTU Master; Custom Request / Responce commands; Custom Produce / Consume transactions; Trigger initiated transactions 7 or 8 data bit; None, Odd, Even Parity; 1 or 2 stop bit; Clear/Freeze

Certifications and Standards

Protection Class IP	IP20
RoHS Compliant	Yes
Recycle / Disposal	TRUE
Product Certifications	CE, UL, WEEE
UL Information	E214107: Ord.Loc UL508, CSA C22.2 No. 14-10; E203225: Haz.Loc CL I DIV2 GP A,B,C,D, ANSI/ISA 12.12.01, CSA C22.2 No. 213
Environment	EN 50082-2, EN 55011, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6
WEEE Category	IT and telecommunications equipment