

Anybus Communicator – Serial Master to Modbus- TCP

Item number: AB7028-C

The Anybus Communicator – Serial Master to Modbus-TCP converts serial protocols to Modbus-TCP, enabling you to connect any RS-232/485 device or equipment to Modbus-TCP control systems. Anybus Communicators ensure reliable, secure, high-speed data transfers between different industrial networks while being easy to use.



Features and benefits

Anybus Communicator – Serial Master to Modbus-TCP



General

Net Weight (g)	300
Packed Width (mm)	15
Packed Height (mm)	6
Packed Depth (mm)	17
Packed Weight (g)	300
Operating Temperature °C Min	0
Operating Temperature °C Max	55
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Relative Humidity	0-95% non condensing
Current Consumption Type Value at Vcc Nom (mA)	100mA @ 24V DC
Current Consumption Max value at Vcc nom (mA)	300mA @ 24V DC
Input Voltage (V)	24V DC (-10% to +10%)
Power Connector	2-pin, 5.08 Phoenix plug connector
Reverse Polarity Protection	Yes
Short Circuit Protection	Yes
Isolation	TRUE
Maximum Installation Altitude (m)	up to 2 000 m
Mounting	DIN-rail (EN 50022 standard)

Anybus Communicator – Serial Master to Modbus-TCP



General

Housing Materials	PC ABS, UL 94
-------------------	---------------

Packaging Material	Cardboard
--------------------	-----------

Identification and Status

Product ID	AB7028-C
------------	----------

Successor	ABC3028-A
-----------	-----------

Country of Origin	Sweden
-------------------	--------

HS Code	8517620000
---------	------------

Dual Usage	No
------------	----

Physical Features

Connectors / Input / Output	1x D-sub 9-pin female, 2xRJ45
-----------------------------	-------------------------------

Contains Battery	No
------------------	----

Modbus-RTU Features

Modbus-RTU Mode	Client / Master
-----------------	-----------------

Modbus-RTU Supported Functionality	RS-232; RS-422; RS485; DF1; Standard Modbus RTU Master; Custom Request / Response commands; Custom Produce / Consume transactions; Trigger initiated transactions 7 or 8 data bit; None, Odd, Even Parity; 1 or 2 stop bit; Clear/Freeze
------------------------------------	--

Modbus-RTU Functions Supported	1, 2, 3, 4, 5, 6, 7, 8, 11, 12, 15, 16, 17, 20, 21, 22, 24
--------------------------------	--

Modbus-RTU Baud Rate	1200,1800,2400,4800,7200,9600,14400,19200,35700,38400,57600 bit/s
----------------------	---

Modbus-RTU Input Data Size	512 bytes
----------------------------	-----------

Modbus-RTU Output Data Size	512 bytes
-----------------------------	-----------

Modbus-TCP Features

Modbus-TCP Mode	Slave / Server
-----------------	----------------

Modbus-TCP Supported Functionality	Modbus specification V1.0; Daisy chaining; QoS; Modbus TCP class 0, class 1 and partially class 2 slave functionality
------------------------------------	---

Modbus-TCP Bandwidth	10/100 Mbit/s
----------------------	---------------

Modbus-TCP Input Data Size	512 bytes
----------------------------	-----------

Anybus Communicator – Serial Master to Modbus-TCP



Modbus-TCP Features

Modbus-TCP Output Data Size	512 bytes
-----------------------------	-----------

Serial Features

Connector	1x D-sub 9-pin female
Max Nodes	31
Baud Rate	1200,1800,2400,4800,7200,9600,14400,19200,35700,38400,57600 bit/s
Supported Functionality	RS-232; RS-422; RS485; DF1; Standard Modbus RTU Master; Custom Request / Response commands; Custom Produce / Consume transactions; Trigger initiated transactions 7 or 8 data bit; None, Odd, Even Parity; 1 or 2 stop bit; Clear/Freeze

Certifications and Standards

Protection Class IP	IP20
RoHS Compliant	Yes
Recycle / Disposal	TRUE
Product Certifications	CE, UL, WEEE
UL Information	E214107: Ord.Loc UL508, CSA C22.2 No. 14-10; E203225: Haz.Loc CL I DIV2 GP A,B,C,D, ANSI/ISA 12.12.01, CSA C22.2 No. 213
Environment	EN 50082-2, EN 55011, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6
WEEE Category	IT and telecommunications equipment