



Anybus EtherMIRROR 1G

Item number: 513-00032

The EtherMIRROR 1G is a transparent measuring point for any industrial network running on PROFINET or EtherNet/IP.

Enable quick measuring access points within your industrial network.

Features and benefits

✓ **Full-duplex mirror port for immediate access**

The EtherMIRROR allows easy tap access points within your network for mobile monitoring or troubleshooting with a single cable

✓ **Compatible for network up to 1Gbit network speed**

The EtherMIRROR can be easily deployed in your Industrial network running on PROFINET, EtherNet/IP and/or Industrial Ethernet.

Anybus EtherMIRROR 1G



General

Net Weight (g)	413
Packed Width (mm)	15
Packed Height (mm)	6
Packed Depth (mm)	22
Packed Weight (g)	416
Operating Temperature °C Min	0
Operating Temperature °C Max	70
Storage Temperature °C Min	-40
Storage Temperature °C Max	120
Current Consumption Type Value at Vcc Nom (mA)	90 mA
Current Consumption Max value at Vcc nom (mA)	90 mA
Power Consumption (W)	90 mA
Input Voltage (V)	20 - 30 VDC
Power Wire Diameter (mm)	< 2.5 mm ²
Reverse Polarity Protection	Yes
Mounting	DIN rail mount (bracket included)
Housing Materials	Aluminium
Packaging Material	Cardboard
Warranty (years)	1 Year

Anybus EtherMIRROR 1G



Identification and Status

Product ID	513-00032
Country of Origin	France
HS Code	8471800000
Dual Usage	No

Physical Features

Contains Battery	No
------------------	----

Certifications and Standards

Protection Class IP	IP20
WEEE Category	IT and telecommunications equipment