



## Anybus CompactCom 30 Module CC-Link

Item number: AB6211-B

The Anybus CompactCom 30 CC-Link is a communication interface that can be embedded into any industrial device or machine to enable communication with CC-Link networks. The module version includes connectors to simplify installation, helping you achieve a fast time to market.



*Enable communication between industrial devices and CC-Link networks*

### Features and benefits



| General                                       |                                                      |
|-----------------------------------------------|------------------------------------------------------|
| Net Width (mm)                                | 50                                                   |
| Net Height (mm)                               | 22                                                   |
| Net Depth (mm)                                | 52                                                   |
| Net Weight (g)                                | 31                                                   |
| Packed Width (mm)                             | 8                                                    |
| Packed Height (mm)                            | 3                                                    |
| Packed Depth (mm)                             | 7                                                    |
| Packed Weight (g)                             | 45                                                   |
| Operating Temperature °C Min                  | -40                                                  |
| Operating Temperature °C Max                  | 70                                                   |
| Storage Temperature °C Min                    | -40                                                  |
| Storage Temperature °C Max                    | 85                                                   |
| Current Consumption Class (CompactCom series) | B                                                    |
| Input Voltage (V)                             | 3.3 VDC, +/- 0.15 VDC                                |
| Application Interface                         | 8-bit parallel (30 ns access) UART (max 625kbps)     |
| Isolation                                     | Galvanic Isolation                                   |
| Content of Delivery                           | CompactCom M30 module                                |
| Mounting                                      | PCB mounting via a customized CompactFlash connector |
| Warranty (years)                              | 1                                                    |



## Identification and Status

|                   |            |
|-------------------|------------|
| Product ID        | AB6211-B   |
| Successor         | AB6602-C   |
| Country of Origin | Sweden     |
| HS Code           | 8517620000 |
| Dual Usage        | No         |

## Physical Features

|                             |                                             |
|-----------------------------|---------------------------------------------|
| Connectors / Input / Output | Pluggable Screw Terminal                    |
| LED Indicators              | Indicates Module Status and Network Status. |
| Form Factor                 | Module                                      |
| Contains Battery            | No                                          |

## Certifications and Standards

|                        |          |
|------------------------|----------|
| Protection Class IP    | IP20     |
| RoHS Compliant         | Yes      |
| Product Certifications | RoHS, UL |
| UL Information         | E214107  |