



Anybus CompactCom Connector Board - CC-Link

Item number: AB6665-B

Used together with the CompactCom Brick to get quick and easy access to network connectors.



Network connectors - ready for use together with the CompactCom Brick

Features and benefits

- ✓ **Easy mounting**
Incorporates a male strip connector - pluggable and solderable.
- ✓ **Modular**
Mix and match CompactCom Bricks and connector boards to give your host application access to different networks.
- ✓ **Robust**
Safe and secure mounting of the brick interface to the host PCB design.
- ✓ **Compatible with Starter Kit**
Used together with the Anybus CompactCom Starter Kit (Brick version) to get access to the right network connectors.

Anybus CompactCom Connector Board - CC-Link



General

Net Width (mm)	40
Net Height (mm)	16
Net Depth (mm)	35
Net Weight (g)	15
Packed Weight (g)	15
Operating Temperature °C Min	-40
Operating Temperature °C Max	85
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Isolation	Galvanic Isolation
Content of Delivery	Connector board
Not Included (in delivery)	Female strip connector, stand-off spacer
Mounting	PCB mounting via a customized CompactFlash connector
Warranty (years)	1 year

Identification and Status

Product ID	AB6665-B
Country of Origin	Sweden
HS Code	8517620000
Dual Usage	No

Physical Features

Connectors / Input / Output	1x 5-pin 5.08 MSTBA
-----------------------------	---------------------

Anybus CompactCom Connector Board - CC-Link



Physical Features

Contains Battery	No
------------------	----



Use Case

