

Anybus Bolt Ethernet 18-pin starter kit

Item number: AWB2300-B

The Anybus Wireless Bolt Ethernet 18-pin starter kit simplifies testing with the Anybus Wireless Bolt, enabling you to connect to Ethernet-based machines via Bluetooth[®], Bluetooth Low Energy, or Wi-Fi. Designed for multi-directional applications, it's ideal for establishing wireless connections with roaming machines, such as AGVs or control cabinets from any angle.



Quick and easy way to try out the Anybus Wireless Bolt

Features and benefits

- ✓ **Industrial design**
Withstands harsh environments thanks to its IP66/67-rated enclosure and wide operating temperature range. Certified for UL Haz.Loc. Class 1/ Div2 and ATEX Zone 2 (Gas).
- ✓ **Designed for multi-directional applications**
Ideal for establishing wireless connections to roaming machines, such as AGVs, or to control cabinets from any angle.
- ✓ **Quick start up and high determinism**
Ideal for connecting field-level devices that require short start-up times and high determinism.
- ✓ **Supports Industrial Ethernet, TCP, & UDP protocols**
Communicates over Industrial Ethernet, supporting protocols such as BACnet/IP, PROFINET, EtherNet/IP, Modbus TCP, as well as all TCP and UDP-based protocols.
- ✓ **Easy to install**
Attach the Wireless Bolt directly onto cabinets or machines to look like an integrated part of the installation. Or use the Bolt Base Protector mounting kit to install it on a pole, wall, or similar.
- ✓ **Insights into your network**
The Command Line Interface (CLI) provides configuration and diagnostic capabilities, offering greater control and insight into your network.
- ✓ **High-speed, roaming, dual network bridging**
Provides fast roaming (IEEE 802.11r) and high link speeds (IEEE 802.11n). Simultaneous Bluetooth and Wireless LAN operation allows bridging between the two networks for enhanced connectivity.
- ✓ **Easy access to data**
Wirelessly connect to the Anybus Bolt and easily access the machine or cabinet. Configure the PLC or machine without halting or hindering production.
- ✓ **All-in-one wireless communication**
All-in-one package featuring a connector, communication processor, and integrated antenna in the same unit. Use the same connector (2x9pPlug Connector) for both power and communication.
- ✓ **Low total cost of ownership**
Thanks to the integrated design of the antenna and communication module, there's no need for additional antenna or accessory purchases.
- ✓ **Easy to configure**
Establish a wireless connection in seconds thanks to the intuitive web-based interface.
- ✓ **Perfect together!**
Fully compatible with Anybus Wireless Bridge, a wireless product designed for point-to-point applications, enabling you to implement comprehensive wireless infrastructure.



General

Related Accessories	024709-B,024708-B
Net Weight (g)	950
Net Dimensions (mm)	68 x 75 (Ø X H) Height above mounting surface: 42.
Packed Width (mm)	17
Packed Height (mm)	12
Packed Depth (mm)	25
Packed Weight (g)	970
Operating Temperature °C Min	-40
Operating Temperature °C Max	65
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Power Consumption (W)	1.7
Input Voltage (V)	9-30
Power Connector	3-pole
Reverse Polarity Protection	Yes
Housing Materials	Plastic
Packaging Material	Cardboard

Identification and Status

Product ID	AWB2300-B
Model Code	AWB2AA



Identification and Status

Country of Origin	Sweden
HS Code	8517620000
Dual Usage	No

Physical Features

Connectors / Input / Output	18-pin connection
Contains Battery	No

Wi-Fi Features

Operation Mode	Access Point, Client
RF Output Power	18 dBm EIRP (including antenna gain 3dBi)
Max No. Of Connections, Access Point	7
Security	WPA2 Personal; WPA2 Enterprise
Net Data Throughput	20 Mbps

Bluetooth Features

Operation Mode	Access Point, Client
Max No. Of Connections	7
Bluetooth Version	Classic Bluetooth v2.1
Net Data Throughput	20 Mbps

Bluetooth Low Energy Features

Operation Mode (LE)	Access Point, Client
RF Output Power (LE)	14 dBm EIRP (including max antenna gain 3 dBi)
Max No. Of Connections (LE)	7
Bluetooth Version (LE)	Bluetooth v4.0
Net Data Throughput (LE)	1Mbps



Certifications and Standards

Protection Class IP	IP66, IP67
Product Certifications	CE, FCC, IC, UL, ATEX
Vibration and Shock	Sinosodial vibration test according to IEC 60068-2-6:2007 and with extra severities; Number of axes: 3 mutually perpendicular (X:Y:Z), Duration: 10 sweep cycles in each axes, Velocity: 1 oct/min, Mode: in operation, Frequency: 5-500 Hz, Displacement ± 3.5 mm, Acceleration: 2g. Shock test according to IEC 60068-2-27:2008 and with extra severities; Wave shape: half sine, Number of shocks: ± 3 in each axes, Mode: In operation, Axes $\pm X,Y,Z$, Acceleration: 30 m/s ² , Duration: 11 ms.
Environment	EN 61000-6-2:2019 EN 61000-4-2:2009 EN 61000-4-3:2006 + A1:2008 + A2:2010 EN 61000-4-4:2012 EN 61000-4-5:2014 EN 61000-4-6:2014 EN 61000-6-4:2019 EN 55016-2-3:2017 EN 55032:2015 EN 301 489-1 V2.2.3 EN 301 489-17 V3.1.1