

Bosch Commercial & VRF systems to KNX Interface

Item number: INKNXACA001I000

The Bosch-KNX interface allows full bidirectional communication between Bosch Commercial and VRF systems and KNX installations. It connects directly to the indoor unit and delivers complete interoperability with KNX.



Bosch to KNX - 1 indoor unit

Features and benefits

- ✓ **ETS configuration**
The interface is configured using the ETS standard configuration tool software.
- ✓ **Multiple energy efficiency functions available**
Timeout, open window, or occupancy energy-saving functions are available to reduce energy costs.
- ✓ **Total unit control and monitoring from KNX**
Through internal variables, running hours counter (for maintenance purposes), and error indication.
- ✓ **Compact dimensions, allowing inside installation**
The interface can be quickly installed inside the AC unit thanks to its reduced dimensions.
- ✓ **Compatible with all KNX thermostats in the market**
All the required DPT objects to be compatible with all KNX thermostats in the market are available.
- ✓ **Smooth KNX thermostat integration**
KNX thermostats are allowed to control the AC unit via the thermostat's temperature sensor.
- ✓ **AC unit control by both remote controller and KNX**
The AC unit can be simultaneously controlled by the manufacturer's remote controller and KNX.

Bosch Commercial & VRF systems to KNX Interface



General	
Capacity	1 indoor unit
Net Width (mm)	71
Net Height (mm)	71
Net Depth (mm)	27
Net Weight (g)	70
Packed Width (mm)	122
Packed Height (mm)	67
Packed Depth (mm)	93
Packed Weight (g)	127
Operating Temperature °C Min	0
Operating Temperature °C Max	60
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Power Consumption (W)	5.8
Input Voltage (V)	29 VDC
Power Connector	2-pole
Configuration	ETS Database
Installation Conditions	This gateway is designed to be mounted inside an enclosure. If the unit is mounted outside an enclosure, precautions should always be taken to prevent electrostatic discharge to the unit. When working inside an enclosure (e.g., making adjustments, setting switches, etc.), typical anti-static precautions should always be followed before touching the unit.
AC Model Compatibility	Commercial AC & VRF systems

Bosch Commercial & VRF systems to KNX Interface



General

Content of Delivery	Intesis Gateway, Installation Manual.
Housing Materials	Plastic
Warranty (years)	3 years
Packaging Material	Cardboard

Identification and Status

Product ID	INKNXACA001I000
Country of Origin	Spain
HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN) (Applies only to the U.S)	EAR99

Physical Features


Connectors / Input / Output	KNX, HVAC port.
LED Indicators	KNX
Contains Battery	No

Certifications and Standards

CE	Yes
CB	Yes
KNX	Yes
WEEE Category	IT and telecommunications equipment



Use Case



Integration example.