



Anybus CompactCom 40 Module DeviceNet

Item number: AB6601-C

The Anybus CompactCom 40 DeviceNet is a communication interface that can be embedded into any industrial device or machine to enable communication with DeviceNet networks. The module version includes connectors to simplify installation, helping you achieve a fast time to market.



Enable communication between industrial devices and DeviceNet networks

Features and benefits

- ✓ **High performance**
Powered by the award-winning NP40 network processor, the Anybus CompactCom guarantees fast data transfer and low latency, making it ideal for the most demanding industrial applications.
- ✓ **Quick time to market**
HMS provides comprehensive support throughout the integration journey, ensuring a quick time to market.
- ✓ **Life cycle management**
HMS maintains every part of the Anybus CompactCom, including network updates, throughout the product's lifecycle.
- ✓ **Easy to install**
Installing the Anybus CompactCom module is a breeze—simply slide it into the host slot. This user-friendly process can be completed by the end-user.
- ✓ **Supports hardware changes**
Possible to swap or install late in the manufacturing process.
- ✓ **Versatile Event-Based Hardware Interfaces**
Enjoy fast and flexible event-based application hardware interfaces with the option to choose from 8/16-bit parallel or high-speed SPI, and I/O via the shift register interface.
- ✓ **ODVA pre-certified**
Pre-certified with ODVA for network compliance, enabling faster network certification.
- ✓ **Complete communication interface**
The Anybus CompactCom module is a complete communication interface, equipped with connectors that simplify integration. Enjoy an all-in-one solution with easy interchangeability.
- ✓ **Robust Security Measures**
Mandatory software signatures prevent unauthorized downloads to the Anybus CompactCom, while robust encryption techniques safeguard against illicit copying.



General

Net Width (mm)	50
Net Height (mm)	22
Net Depth (mm)	52
Net Weight (g)	31
Packed Width (mm)	8
Packed Height (mm)	3
Packed Depth (mm)	7
Packed Weight (g)	40
Operating Temperature °C Min	-40
Operating Temperature °C Max	70
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Class (CompactCom series)	B
Current Consumption Max value at Vcc nom (mA)	up to 500 mA
Input Voltage (V)	3.3 VDC, +/- 0.15 VDC
Application Interface	Parallel 8/16-bit (30 ns access). High speed SPI (baudrate configurable up to 20 MHz). Shift register interface (cyclical update time 82 µs). UART (for backwards compatibility with 30-series, max 625kbps).
Isolation	Galvanic Isolation
Content of Delivery	CompactCom M40 module
Mounting	PCB mounting via a customized CompactFlash connector



General

Warranty (years)	1 year
------------------	--------

Identification and Status

Product ID	AB6601-C
Country of Origin	Sweden
HS Code	8517620000
Dual Usage	No

Physical Features

Connectors / Input / Output	1x 5-pin 5.08 MSTBA
LED Indicators	Integrated on front. Indicates Module Status and Network Status.
Form Factor	Module
Contains Battery	No

DeviceNet Features

DeviceNet Mode	Adapter
DeviceNet Supported Functionality	CIP Parameter Object Support. Explicit messaging. UCMM Capable. Bit-strobed I/O. Change-of-state / Cyclic I/O. Polled I/O. Automatic Baud Rate Detection. Quick Connect.
DeviceNet Configuration File	EDS available
DeviceNet Baud Rate	125-500 kbps
DeviceNet Input Data Size	512 bytes
DeviceNet Output Data Size	512 bytes

Certifications and Standards

RoHS Compliant	Yes
Product Certifications	RoHS, UL
UL Information	E214107