

Anybus EtherNet/IP to PROFIBUS Linking Device

Item number: HMS-EN2PB-R

The Anybus EtherNet/IP to PROFIBUS Linking Device converts PROFIBUS to EtherNet/IP, enabling you to connect any PROFIBUS device to a Logix PLC control system. The linking device presents PROFIBUS data as easily processed I/O data, offloading the PLC from working with extra calculations and allowing for seamless integration with Studio 5000.



Enable seamless integration of serial devices to Studio 5000

Features and benefits

✓ Seamless integration with Studio 5000

The unique Studio 5000[®] Logix designer integration provides access to everything, including serial network configuration. No need for extra 3rd-party software, licenses, or programming.

✓ Automatic tag names

Our Custom Add-On Profile for Studio 5000 supports the automatic generation of named and structured controller tags, eliminating the need to create alias tags.

✓ No programming required

Easy to set up with the Custom Add-On Profile. No programming required!

✓ Trusted partner

Anybus has a long history of working with all the major network organizations to ensure compliant, high-performing, and compatible products.

✓ Life cycle management

HMS maintains every part of the Linking Devices, including network updates, throughout the product's lifecycle.

✓ Connect, configure, done

EtherNet/IP Linking Devices are configured using a Custom Add-On Profile in Studio 5000, dynamically generating data structures for each device and eliminating the need for ladder logic files.

✓ 3-year warranty

The linking devices are designed to be robust and long-lasting. A 3-year guarantee is provided.

✓ Increased performance - Logix PLC

Presents serial data as easily processed I/O data offloading the Logix PLC from extra calculations.

✓ Life cycle management

HMS maintains every part of the Linking Devices, including network updates, throughout the product's lifecycle.



Anybus EtherNet/IP to PROFIBUS Linking Device

General

Net Width (mm)	35
Net Height (mm)	110
Net Depth (mm)	101
Net Weight (g)	155
Packed Width (mm)	14
Packed Height (mm)	6
Packed Depth (mm)	17
Packed Weight (g)	320
Operating Temperature °C Min	-25
Operating Temperature °C Max	60
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Type Value at Vcc Nom (mA)	200mA @ 24V DC
Current Consumption Max value at Vcc nom (mA)	300mA @ 24V DC
Input Voltage (V)	24V DC (-15% to +20%)
Power Connector	3-pin, 5.08 Phoenix plug connector
Isolation	TRUE
Mounting	DIN-rail (EN 50022 standard)
Housing Materials	PC ABS, UL 94 VO



Anybus EtherNet/IP to PROFIBUS Linking Device

General

Packaging Material	Cardboard
--------------------	-----------

Identification and Status

Product ID	HMS-EN2PB-R
Country of Origin	Sweden
HS Code	8517620000
Dual Usage	No

Physical Features

Contains Battery	No
------------------	----

EtherNet/IP Features

EtherNet/IP Mode	Adapter / Slave
EtherNet/IP Supported Functionality	Preinstalled Add On Profile in Studio 5000 Logix Designer
EtherNet/IP Configuration File	EDS available
EtherNet/IP Bandwidth	10/100MBit
EtherNet/IP Input Data Size	3500 bytes over 10 connections
EtherNet/IP Output Data Size	3500 bytes over 10 connections

PROFIBUS Features

PROFIBUS Mode	Master
PROFIBUS Supported Functionality	PROFIBUS DP Master functionality according to IEC 61158;Acyclic Communication (DP-V1, Class 1 & 2);LiveList;ControlStatus
PROFIBUS Device Address	0-125
PROFIBUS Baud Rate	9600 bit/s - 12 Mbit/s
PROFIBUS Input Data Size	3500 bytes
PROFIBUS Output Data Size	3500 bytes

Certifications and Standards

Protection Class IP	IP20
---------------------	------



Anybus EtherNet/IP to PROFIBUS Linking Device

Certifications and Standards	
RoHS Compliant	Yes
Recycle / Disposal	TRUE
Product Certifications	CE, UL, WEEE, RoHS
WEEE Category	IT and telecommunications equipment