

Anybus X-gateway – PROFIBUS Slave – PROFIBUS Slave

Item number: AB7843-F

The Anybus X-gateway PROFIBUS Slave to PROFIBUS Slave enables you to connect any PROFIBUS system to any PROFIBUS control system. Anybus gateways ensure reliable, secure, high-speed data transfers between different industrial networks while being easy to use.



A protocol converter that connects PROFIBUS and PROFIBUS control systems

Features and benefits

- ✓ **Reach new markets**
Target new markets using different protocols without needing to change your hardware or software, thereby decreasing your time to market and development costs.
- ✓ **Slim hardware design**
The gateway is designed for IP20 and DIN-rail mounting, enabling you to install it with ease, close to connected devices, thereby reducing wiring requirements.
- ✓ **Easy configuration – No programming required!**
Quickly establish the connection between the two networks with the included Anybus Configuration Manager software. No programming skills are required for the setup process.
- ✓ **Trusted partner**
Anybus has a long history of working with all the major network organizations to ensure compliant, high-performing, and compatible products.
- ✓ **No PLC card slot needed**
The gateway does not use a card slot in the control system, leaving room for other equipment.
- ✓ **3-year warranty**
The gateway is designed to be robust and long-lasting. A 3-year guarantee is provided.
- ✓ **Increased PLC performance**
The gateway allows for fast transfer of cyclic I/O data between the two networks, offloading your PLC from working with additional calculations.
- ✓ **Life cycle management**
HMS maintains every part of the gateway, including network updates, throughout the product's lifecycle.

Anybus X-gateway – PROFIBUS Slave – PROFIBUS Slave



General

Net Width (mm)	44
Net Height (mm)	127
Net Depth (mm)	114
Net Weight (g)	420
Packed Width (mm)	155
Packed Height (mm)	75
Packed Depth (mm)	200
Packed Weight (g)	600
Operating Temperature °C Min	-25
Operating Temperature °C Max	65
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Type Value at Vcc Nom (mA)	200mA @ 24V DC
Current Consumption Max value at Vcc nom (mA)	400mA @ 24V DC
Input Voltage (V)	24V DC (-20% to +20%)
Power Connector	2-pin, 5.08 Phoenix plug connector
Reverse Polarity Protection	Yes
Short Circuit Protection	Yes
Isolation	TRUE

Anybus X-gateway – PROFIBUS Slave – PROFIBUS Slave



General

Mounting	DIN-rail (EN 50022 standard)
Housing Materials	Aluminium, Plastic
Packaging Material	Cardboard

Identification and Status

Product ID	AB7843-F
Country of Origin	Sweden
HS Code	8517620000
Dual Usage	No

Physical Features

Connectors / Input / Output	1x D-sub 9-pin female PROFIBUS connector, USB-B Config port
DIP & Rotary Switches	2x Rotary Address Node
Contains Battery	No

PROFIBUS Features

PROFIBUS Mode	DP Device
PROFIBUS Supported Functionality	PROFIBUS-DP/DPV1 Slave functionality according to extensions of EN 50170; Acyclic Communication (DP-V1, Class 1 & 2); Acyclic User Parameter data / Diagnostics length - up to 237 bytes; Sync; Freeze; Watchdog
PROFIBUS Device Address	0-125
PROFIBUS Configuration File	GSD available
PROFIBUS Baud Rate	9600 bit/s - 12 Mbit/s
PROFIBUS Input Data Size	244 bytes (344 max tot in+out)
PROFIBUS Output Data Size	244 bytes (344 max tot in+out)

Certifications and Standards

Protection Class IP	IP20
RoHS Compliant	Yes

Anybus X-gateway – PROFIBUS Slave – PROFIBUS Slave



Certifications and Standards	
Recycle / Disposal	TRUE
UL Information	E214107: Ord.Loc UL508, CSA C22.2 NO. 142
Environment	EN 61000-6-4, EN 55016-2-3 Class A, EN 55022 Class A, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6
WEEE Category	IT and telecommunications equipment