

Anybus CompactCom 40 Module Without Housing - CC-Link



Item number: AB6702-C

The Anybus CompactCom 40 Without Housing - CC-Link is a communication interface that can be embedded into any industrial device or machine to enable communication with CC-Link networks. The module version includes connectors to simplify installation, helping you achieve a fast time to market.

Enable communication between industrial devices and CC-Link networks

Features and benefits

✓ High performance

Powered by the award-winning NP40 network processor, the Anybus CompactCom guarantees fast data transfer and low latency, making it ideal for the most demanding industrial applications.

✓ Quick time to market

HMS provides comprehensive support throughout the integration journey, ensuring a quick time to market.

✓ Life cycle management

HMS maintains every part of the Anybus CompactCom, including network updates, throughout the product's lifecycle.

✓ Custom look

Delivered without housing, enabling the Anybus CompactCom to be securely integrated behind the front panel of your device, resulting in a customized appearance and seamless design integration.

✓ Supports hardware changes

Possible to swap or install late in the manufacturing process.

✓ Versatile Event-Based Hardware Interfaces

Enjoy fast and flexible event-based application hardware interfaces with the option to choose from 8/16-bit parallel or high-speed SPI, and I/O via the shift register interface.

✓ CLPA pre-certified

Pre-certified with CLPA for network compliance, enabling faster network certification.

✓ Complete communication interface

The Anybus CompactCom module is a complete communication interface, equipped with connectors that simplify integration. Enjoy an all-in-one solution with easy interchangeability.

✓ Robust Security Measures

Mandatory software signatures prevent unauthorized downloads to the Anybus CompactCom, while robust encryption techniques safeguard against illicit copying.

Anybus CompactCom 40 Module Without Housing - CC-Link



General

Net Width (mm)	37
Net Height (mm)	16
Net Depth (mm)	51
Net Weight (g)	30
Packed Weight (g)	30
Operating Temperature °C Min	-40
Operating Temperature °C Max	85
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Class (CompactCom series)	B
Current Consumption Max value at Vcc nom (mA)	up to 500 mA
Input Voltage (V)	3.3 VDC, +/- 0.15 VDC
Application Interface	Parallel 8/16-bit (30 ns access). High speed SPI (baudrate configurable up to 50 MHz). Shift register interface (cyclical update time 82 µs). UART (for backwards compatibility with 30-series, max 625kbps).
Isolation	Galvanic Isolation
Content of Delivery	CompactCom M40 module (without housing)
Mounting	PCB mounting via a CompactFlash connector
Warranty (years)	1 year

Identification and Status

Product ID	AB6702-C
Country of Origin	Sweden

Anybus CompactCom 40 Module Without Housing - CC-Link



Identification and Status

HS Code	8517620000
Dual Usage	No

Physical Features

Connectors / Input / Output	1x 5-pin 5.08 MSTBA
LED Indicators	Semi-Integrated. RUN and Error via application interface or external light pipes
Form Factor	Module without Housing
Contains Battery	No

CC-Link Features

CC-Link Mode	CC-link Remote Device
CC-Link Supported Functionality	CC-Link v.1.10 (default), CC-Link v.2.00. Automatic CC-Link system handshaking.
CC-Link Configuration File	CSP available
CC-Link Baud Rate	Common Baudrates up to 10 Mbps
CC-Link Output Data Size	368 bytes (CC-Link v.2.00)
CC-Link Input Data Size	368 bytes (CC-Link v.2.00)

Certifications and Standards

RoHS Compliant	Yes
Product Certifications	RoHS, UL
UL Information	E214107