Anybus ComBricks Head Station 1A

Item number: 101-20011A

The Head Station is the primary element of ComBricks and has to be inserted in the most left slot of the fixed backplane socket. It schedules the interaction between all modules and provides data storage and an Ethernet interface for the user.



The primary element of the ComBricks modular system

Features and benefits

The main power source for all

The Head Station provides power to all modules through its redundant power supply.

Supporting multiple networks

Repeater modules can be set to 4 networks.

Remote web server access

Have full data insight into your network measurements such as status of all devices, live lists, statistics, message recordings, PROFIBUS events and more whenever you need it.

Anybus ComBricks Head Station 1A



General

Net Weight (g)	147
Packed Width (mm)	10
Packed Height (mm)	15
Packed Depth (mm)	20
Packed Weight (g)	397
Operating Temperature °C Min	-20
Operating Temperature °C Max	60
Current Consumption Type Value at Vcc Nom (mA)	73 mA
Current Consumption Max value at Vcc nom (mA)	800 mA
Input Voltage (V)	11…26 VDC
Power Wire Diameter (mm)	< 2.5 mm^2
Reverse Polarity Protection	Yes
Mounting	DIN rail mount (bracket included)
Housing Materials	Plastic
Packaging Material	Cardboard
Warranty (years)	1 Year

Identification and Status

Product ID	101-20011A
Country of Origin	Netherlands (the)
HS Code	8471800000

Anybus ComBricks Head Station 1A



Identification and Status

Dual Usage	No

Physical Features

Contains Battery	No

Certifications and Standards

Protection Class IP	IP20
RoHS Compliant	Yes
Product Certifications	CE, UKCA, UL, FCC, EMC, RoHS
WEEE Category	IT and telecommunications equipment