

Anybus CompactCom 40 Module Without Housing - Common Ethernet



Item number: AB6710-E

The Anybus CompactCom 40 Common Ethernet without housing is a communication interface that can be embedded into any industrial device or machine to enable communication with PROFINET, EtherCAT, EtherNet/IP, Modbus TCP, Powerlink, or BACnet/IP networks. The module includes connectors for a fast time to market.

Enable communication between industrial devices and Industrial Ethernet networks

Features and benefits

- ✓ **High performance**
Powered by the award-winning NP40 network processor, the Anybus CompactCom guarantees fast data transfer and low latency, making it ideal for the most demanding industrial applications.
- ✓ **Quick time to market**
HMS provides comprehensive support throughout the integration journey, ensuring a quick time to market.
- ✓ **Life cycle management**
HMS maintains every part of the Anybus CompactCom, including network updates, throughout the product's lifecycle.
- ✓ **Custom look**
Delivered without housing, enabling the Anybus CompactCom to be securely integrated behind the front panel of your device, resulting in a customized appearance and seamless design integration.
- ✓ **Switch networks without changing hardware**
Simply download firmware for PROFINET, EtherCAT, Modbus-TCP, POWERLINK, or EtherNet/IP, ensuring adaptability to industrial network changes without altering hardware.
- ✓ **Versatile Event-Based Hardware Interfaces**
Enjoy fast and flexible event-based application hardware interfaces with the option to choose from 8/16-bit parallel or high-speed SPI, and I/O via the shift register interface.
- ✓ **Pre-certified**
Pre-certified for network compliance for all networks, enabling faster network certification.
- ✓ **Complete communication interface**
The Anybus CompactCom module is a complete communication interface, equipped with connectors that simplify integration. Enjoy an all-in-one solution with easy interchangeability.
- ✓ **Robust Security Measures**
Mandatory software signatures prevent unauthorized downloads to the Anybus CompactCom, while robust encryption techniques safeguard against illicit copying.
- ✓ **Supports hardware changes**
Possible to swap or install late in the manufacturing process.

Anybus CompactCom 40 Module Without Housing - Common Ethernet



General	
Net Width (mm)	37
Net Height (mm)	16
Net Depth (mm)	51
Net Weight (g)	15
Packed Weight (g)	15
Operating Temperature °C Min	-40
Operating Temperature °C Max	85
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Class (CompactCom series)	B
Current Consumption Max value at Vcc nom (mA)	up to 500 mA
Input Voltage (V)	3.3 VDC, +/- 0.15 VDC
Application Interface	Parallel 8/16-bit (30 ns access). High speed SPI (baudrate configurable up to 50 MHz). Shift register interface (cyclical update time 82 µs). UART (for backwards compatibility with 30-series, max 625kbps).
Isolation	Galvanic Isolation
Content of Delivery	CompactCom M40 module (without housing)
Mounting	PCB mounting via a CompactFlash connector
Warranty (years)	1 year
Identification and Status	
Product ID	AB6710-E
Predecessor	AB6710-C, AB6710-D

Anybus CompactCom 40 Module Without Housing - Common Ethernet



Identification and Status

Country of Origin	Sweden
HS Code	8517620000
Dual Usage	No

Physical Features

Connectors / Input / Output	2x RJ45
LED Indicators	Semi-Integrated. Link/Activity are available on RJ45 connectors. Module Status and Network Status via application interface or external light pipes
Form Factor	Module without Housing
Contains Battery	No

Certifications and Standards

RoHS Compliant	Yes
UL Information	E214107