

Anybus Communicator PROFIBUS DP Device - Common Ethernet

Item number: ABC4091-A

The Anybus Communicator PROFIBUS DP Device to Common Ethernet enables you to connect any PROFIBUS DP control system to any PROFINET, EtherCAT, EtherNet/IP, or Modbus TCP control systems. Anybus Communicators ensure reliable, secure, high-speed data transfers between different industrial networks. They include built-in cybersecurity features and are compliant with the Cyber Resilience Act (CRA). Thanks to our intuitive web-based user interface, they're also incredibly easy to use.



A protocol converter that connects PROFIBUS DP and Industrial Ethernet control systems

Features and benefits

- ✓ **Transfer up to 1500 bytes to and from the controller (PLC)**
Transfer up to 1500 bytes (network dependent) in each direction (3000 bytes total) via dual 10/100 Mbit full duplex RJ45 ports with an integrated switch for daisy-chaining.
- ✓ **Transfer 244 bytes to and from PROFIBUS controller (PLC)**
Transfer up to 244 bytes in each direction (488 bytes total). PROFIBUS DP device (slave) with automatic baud rate detection. Address setting via rotary switches or web interface. Includes a GSD file.
- ✓ **Selectable Industrial Ethernet network**
Cover multiple protocols with a single Communicator. Supports EtherNet/IP, EtherCAT, Modbus TCP, and PROFINET. Download firmware for your desired protocols from the product webpage and upload it via the Communicator's interface.
- ✓ **Instant data transfer**
The Communicator transfers data instantly between networks, with processing time so low you don't even need to count it, as it's in line with network jitter. Just add the cycle times of both networks to get the total transfer time.
- ✓ **Configure via web interface over Ethernet**
With a graphical and responsive web interface, configuration is a breeze. In addition, there's no software to install and the dedicated Ethernet configuration port makes it easy to get started.
- ✓ **Diagnostics and support**
The user interface shows connection status, allowing you to monitor the data going through the gateway. Monitor and control offline behavior via the Status Byte and Clear Data features. Our global support team is ready to help if needed.
- ✓ **Drop-in replacement**
Already using an X-gateway? Don't worry, with legacy mode you can continue using the same configuration in your controller/PLC.
- ✓ **Secure and segment networks**
Secure boot blocks malware, while a security switch locks configurations to prevent unauthorized changes. Network segmentation is inherent in the design, as each network is run separately, with only configured data transferred between networks.
- ✓ **Built for factory floors**
The Gateway is made with industrial-grade components, verified to meet industry standards, and backed by a 5-year warranty. Its slim form factor, front-facing ports, and cable tie make DIN-rail installation easy.
- ✓ **Cyber Resilience Act (CRA)-ready**
Developed under an IEC 62443-4-1 certified process, with HTTPS configuration, role-based access control, and a physical security switch to help meet CRA requirements.

Anybus Communicator PROFIBUS DP Device - Common Ethernet



General

Net Width (mm)	27
Net Height (mm)	144
Net Depth (mm)	98
Net Weight (g)	150
Packed Width (mm)	35
Packed Height (mm)	170
Packed Depth (mm)	115
Packed Weight (g)	185
Operating Temperature °C Min	-25
Operating Temperature °C Max	70
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Type Value at Vcc Nom (mA)	90mA @ 24V DC (2.2W)
Current Consumption Max value at Vcc nom (mA)	125mA @24V DC (3W)
Input Voltage (V)	12-30V DC
Power Connector	3-pin, 5.08 Phoenix plug connector
Reverse Polarity Protection	Yes
Short Circuit Protection	Yes
Isolation	TRUE

Anybus Communicator PROFIBUS DP Device - Common Ethernet



General

Content of Delivery	Gateway, power connector, start-up guide, compliance information sheet
Mounting	DIN-rail (EN 50022 standard)
Housing Materials	PC ABS, UL 94 VO
Packaging Material	Cardboard
Warranty (years)	5

Identification and Status

Product ID	ABC4091-A
Model Code	40-ETH-PDP-A
Predecessor	AB7832-F, AB7634-F, AB7685-F, AB7652-F
Country of Origin	Sweden
HS Code	8517620000
Dual Usage	No

Physical Features

Connectors / Input / Output	2xRJ45, 2xRJ45, 2xRJ45, 2x RJ45, 1x D-sub 9-pin female PROFIBUS connector, RJ45 Config port
Push Buttons	Factory reset
Contains Battery	No

EtherCAT Features

EtherCAT Mode	Slave / SubDevice
EtherCAT Supported Functionality	COE (Can Over EtherCAT); PDO, SDO; APRD, ARMW, APWR, BRD, BWR, FPRD, FPRW, FPWR, FRMW, LRD, LRW, LWR
EtherCAT Configuration File	ESI available
EtherCAT Bandwidth	10/100 Mbit down to 100us cycle time
EtherCAT Input Data Size	1486 bytes

Anybus Communicator PROFIBUS DP Device - Common Ethernet



EtherCAT Features

EtherCAT Output Data Size	1486 bytes
---------------------------	------------

EtherNet/IP Features

EtherNet/IP Mode	Adapter / Slave
EtherNet/IP Supported Functionality	Endian conversion (byte swap); QoS; Ethernet/IP Class 1 and 3; Quick Connect Class B; DLR (beacon mode); Daisy Chainging; CT19 ODVA Conformance
EtherNet/IP Configuration File	EDS available
EtherNet/IP Bandwidth	10/100MBit down to 1ms cycle time
EtherNet/IP Input Data Size	1448 bytes
EtherNet/IP Output Data Size	1448 bytes

Modbus-TCP Features

Modbus-TCP Mode	Slave / Server
Modbus-TCP Supported Functionality	Modbus specification V1.1b3; 4 connections; Daisy chaining
Modbus-TCP Functions Supported	1, 2, 3, 4, 5, 6, 15, 16, 23, 43/14
Modbus-TCP Bandwidth	10/100 Mbit/s
Modbus-TCP Input Data Size	1500 bytes
Modbus-TCP Output Data Size	1500 bytes

PROFIBUS Features

PROFIBUS Mode	DP Device
PROFIBUS Supported Functionality	PROFIBUS-DP Slave functionality according to extensions of EN 50170
PROFIBUS Device Address	0-125
PROFIBUS Configuration File	GSD available
PROFIBUS Baud Rate	9600 bit/s - 12 Mbit/s
PROFIBUS Input Data Size	244 bytes

Anybus Communicator PROFIBUS DP Device - Common Ethernet



PROFIBUS Features

PROFIBUS Output Data Size	244 bytes
---------------------------	-----------

PROFINET Features

PROFINET Mode	Slave
---------------	-------

PROFINET Supported Functionality	RT; Daisy chaining;
----------------------------------	---------------------

PROFINET Conformance Class	Class B
----------------------------	---------

PROFINET Configuration File	GSDML available
-----------------------------	-----------------

PROFINET Bandwidth	10/100MBit down to 1ms cycle time
--------------------	-----------------------------------

PROFINET Input Data Size	1024 bytes
--------------------------	------------

PROFINET Output Data Size	1024 bytes
---------------------------	------------

Certifications and Standards

Protection Class IP	IP20
---------------------	------

Product Certifications	CE, UL, KC, WEEE, EMC
------------------------	-----------------------


UL Information	E214107: Ord.Loc UL 61010-1, CSA C22.2 No. 61010-1, UL 61010-2-201, CSA C22.2 No. 61010-2-201
----------------	---

Environment	EN 55016-2-3 Class A, EN 55032 Class A, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6
-------------	--

WEEE Category	IT and telecommunications equipment
---------------	-------------------------------------



Use Case



The communicator can be used wherever there is a need to transfer data between control systems using different industrial protocols.