

Anybus X-gateway – PROFIBUS Slave - J1939

Item number: AB7615-C

The Anybus X-gateway PROFIBUS Slave to J1939 enables you to connect any PROFIBUS system to any J1939 control system. Anybus gateways ensure reliable, secure, high-speed data transfers between different industrial networks while being easy to use.



A protocol converter that connects PROFIBUS and J1939 control systems

Features and benefits

- ✓ **Reach new markets**
Target new markets using different protocols without needing to change your hardware or software, thereby decreasing your time to market and development costs.
- ✓ **Slim hardware design**
The gateway is designed for IP20 and DIN-rail mounting, enabling you to install it with ease, close to connected devices, thereby reducing wiring requirements.
- ✓ **Easy configuration – No programming required!**
Quickly establish the connection between the two networks with the included Anybus Configuration Manager software. No programming skills are required for the setup process.
- ✓ **Trusted partner**
Anybus has a long history of working with all the major network organizations to ensure compliant, high-performing, and compatible products.
- ✓ **No PLC card slot needed**
The gateway does not use a card slot in the control system, leaving room for other equipment.
- ✓ **3-year warranty**
The gateway is designed to be robust and long-lasting. A 3-year guarantee is provided.
- ✓ **Increased PLC performance**
The gateway allows for fast transfer of cyclic I/O data between the two networks, offloading your PLC from working with additional calculations.
- ✓ **Life cycle management**
HMS maintains every part of the gateway, including network updates, throughout the product's lifecycle.
- ✓



General	
Net Width (mm)	127
Net Height (mm)	44
Net Depth (mm)	114
Net Weight (g)	445
Packed Width (mm)	18
Packed Height (mm)	7
Packed Depth (mm)	14
Packed Weight (g)	525
Operating Temperature °C Min	-25
Operating Temperature °C Max	65
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Type Value at Vcc Nom (mA)	200mA @ 24V DC
Current Consumption Max value at Vcc nom (mA)	400mA @ 24V DC
Input Voltage (V)	24V DC (-20% to +20%)
Power Connector	2-pin, 5.08 Phoenix plug connector
Isolation	TRUE
Mounting	DIN-rail (EN 50022 standard)
Housing Materials	Aluminium



General

Packaging Material	Cardboard
--------------------	-----------

Identification and Status

Product ID	AB7615-C
Country of Origin	Sweden
HS Code	8517620000
Dual Usage	No

Physical Features

Contains Battery	No
------------------	----

PROFIBUS Features

PROFIBUS Mode	Slave
PROFIBUS Supported Functionality	PROFIBUS-DP/DPV1 Slave functionality according to extensions of EN 50170; Acyclic Communication (DP-V1, Class 1 & 2); Acyclic User Parameter data / Diagnostics length - up to 237 bytes; Sync; Freeze; Watchdog
PROFIBUS Device Address	0-125
PROFIBUS Configuration File	GSD available
PROFIBUS Baud Rate	9600 bit/s - 12 Mbit/s
PROFIBUS Input Data Size	244 bytes (344 max tot in+out)
PROFIBUS Output Data Size	244 bytes (344 max tot in+out)

Certifications and Standards

Protection Class IP	IP20
RoHS Compliant	Yes
Recycle / Disposal	TRUE
Product Certifications	CE, UL, WEEE, RoHS
Environment	EN 55011, EN 61000-6-2
WEEE Category	IT and telecommunications equipment