

Anybus X-gateway IIoT – Modbus RTU Slave - OPC UA-MQTT

Item number: AB7561-F

The Anybus X-gateway IIoT Modbus RTU Slave to OPC UA-MQTT publishes process data from any Modbus RTU control system to OPC UA or MQTT information systems.



A protocol converter that connects Modbus RTU to OPC UA-MQTT information systems

Features and benefits

- ✓ **Fast streaming of industrial network data**
Enables the fast streaming of industrial network data into OPC UA and MQTT systems, supporting efficient data transfer.
- ✓ **Secure and isolated data flow**
The gateway ensures that networks and devices remain secure and isolated by controlling data flow through an independent device. This prevents unauthorized access while maintaining reliable communication between systems.
- ✓ **No PLC card slot needed**
The gateway does not use a card slot in the control system, leaving room for other equipment.
- ✓ **3-year warranty**
The gateway is designed to be robust and long-lasting. A 3-year guarantee is provided.
- ✓ **Trusted partner**
Anybus has a long history of working with all the major network organizations to ensure compliant, high-performing, and compatible products.
- ✓ **One-Way data transfer to OPC UA or MQTT**
The gateway transfers data to OPC UA or MQTT information systems, enabling integration with these platforms while ensuring a smooth, uninterrupted data flow.
- ✓ **Reach new markets**
Target new markets using different protocols without needing to change your hardware or software, thereby decreasing your time to market and development costs.
- ✓ **Slim hardware design**
The gateway is designed for IP20 and DIN-rail mounting, enabling you to install it with ease, close to connected devices, thereby reducing wiring requirements.
- ✓ **Easy configuration – No programming required!**
Quickly establish the connection between the two networks with the included Anybus Configuration Manager software. No programming skills are required for the setup process.
- ✓ **Life cycle management**
HMS maintains every part of the gateway, including network updates, throughout the product's lifecycle.

Anybus X-gateway IIoT – Modbus RTU Slave - OPC UA-MQTT



General

Net Width (mm)	44
Net Height (mm)	127
Net Depth (mm)	114
Net Weight (g)	420
Packed Width (mm)	155
Packed Height (mm)	75
Packed Depth (mm)	200
Packed Weight (g)	600
Operating Temperature °C Min	-25
Operating Temperature °C Max	65
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Type Value at Vcc Nom (mA)	200mA @ 24V DC
Current Consumption Max value at Vcc nom (mA)	400mA @ 24V DC
Input Voltage (V)	24V DC (-20% to +20%)
Power Connector	2-pin, 5.08 Phoenix plug connector
Isolation	TRUE
Mounting	DIN-rail (EN 50022 standard)
Housing Materials	Aluminium, Plastic

Anybus X-gateway IIoT – Modbus RTU Slave - OPC UA-MQTT



General

Packaging Material	Cardboard
--------------------	-----------

Identification and Status

Product ID	AB7561-F
Country of Origin	Sweden
HS Code	8517620000
Dual Usage	No

Physical Features

Connectors / Input / Output	2xRJ45, 1x D-sub 9-pin female, USB-B Config port
DIP & Rotary Switches	dip switch Termination and configuraiton
Contains Battery	No

Modbus-RTU Features

Modbus-RTU Mode	Slave mode
Modbus-RTU Supported Functionality	Modbus-RTU compliant passive slave node operation; 256 Modbus registers in each direction; Modbus diagnostics
Modbus-RTU Functions Supported	1, 2, 3, 4, 5, 6, 15, 16, 22, 23
Modbus-RTU Baud Rate	1200bps - 57600bps
Modbus-RTU Input Data Size	512 bytes
Modbus-RTU Output Data Size	512 bytes

Certifications and Standards

Protection Class IP	IP20
RoHS Compliant	Yes
Recycle / Disposal	TRUE
Product Certifications	CE, UL, WEEE, RoHS
UL Information	E214107: Ord.Loc UL508, CSA C22.2 NO. 142

Anybus X-gateway IIoT – Modbus RTU Slave - OPC UA-MQTT



Certifications and Standards	
Environment	EN 61000-6-4, EN 55016-2-3 Class A, EN 55022 Class A, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6
WEEE Category	IT and telecommunications equipment