Mitsubishi Electric City Multi systems to Modbus TCP/RTU Application

Item number: IN770AIR00SO000

The Mitsubishi Electric application has been specially designed to allow bidirectional control and monitoring of Mitsubishi Electric City Multi systems from a BMS, SCADA, PLC, or any other device working as a Modbus client. The solution allows the integration of up to 50 groups from a single interface.

Mitsubishi Electric to Modbus TCP/RTU - Up to 50 groups

Features and benefits

Reduce hardware costs and improve system scalability

The gateway is a Modbus server and can manage both Modbus TCP and Modbus RTU simultaneously.

Automatic identification

A scan function is available for automatic identification of the units present in the VRF system.

Individual indoor unit energy consumption signals

Energy consumption signals from each indoor unit are available, so they can be checked individually.

Commissioning-friendly approach with Intesis MAPS

Templates can be imported and reused as often as needed, significantly reducing commissioning time.

Direct access to the central controller

Communicates via Ethernet with the centralized controllers: G-50, G-50A, GB-50A, GB-50ADA, AB-150, AE-200, AE-50, AE-C400, AE-C400E, AG-150A, EW-50, EW-C50, EB-50GU.

Outdoor unit signals

Signals assigned to the outdoor unit are available to be used in the integration.

Multiple TCP client support

The interface supports up to 6 TCP clients (incoming sockets).

Configuration tool and interface automatic updates

Both the Intesis MAPS configuration tool and the interface's firmware can receive automatic updates.

Mitsubishi Electric City Multi systems to Modbus TCP/RTU Application

General

Capacity	S: Up to 50 groups
Net Width (mm)	106
Net Height (mm)	90
Net Depth (mm)	58
Net Weight (g)	194
Packed Width (mm)	125
Packed Height (mm)	85
Packed Depth (mm)	140
Packed Weight (g)	356
Operating Temperature °C Min	0º
Operating Temperature °C Max	60º
Storage Temperature °C Min	-30
Storage Temperature °C Max	60
Power Consumption (W)	3
Input Voltage (V)	For DC: 12 .. 36 VDC ±10%, Max: 250 mA For AC: 24 VAC ±10 %, 50-60 Hz, Max: 127 mA Recommended voltage: 24 VDC, Max: 127 mA
Power Connector	3-pole
Configuration	Intesis MAPS
Installation Conditions	This gateway is designed to be mounted inside an enclosure. If the unit is mounted outside an enclosure, precautions should always be taken to prevent electrostatic discharge to the unit. When working inside an enclosure (e.g., making adjustments, setting switches, etc.), typical anti-static precautions should always be followed before touching the unit.
AC Model Compatibility	List of compatible centralized controllers: G-50, G-50A, GB-50A, GB-50ADA, AB-150, AE-200, AE-50, AE-C400, AE-C400E, AG-150A, EW-50, EW-C50, EB-50GU.

Mitsubishi Electric City Multi systems to Modbus TCP/RTU Application

General

Content of Delivery	Intesis gateway and installation manual.
Not Included (in delivery)	Power supply not included.
Mounting	DIN rail mount (bracket included), Wall mount
Housing Materials	Plastic
Warranty (years)	3 years
Packaging Material	Cardboard

Identification and Status

Product ID	IN770AIR00SO000_MBS_MIT
Country of Origin	Spain
HS Code	8517620000
Dual Usage	No

Physical Features

Connectors / Input / Output	Power supply, EIA-485, KNX, Ethernet, HVAC port, Binary inputs (dry contact), Console port USB.
LED Indicators	Gateway and communication status.
Push Buttons	Factory reset. I-Am message (for BACnet only). Normal mode/programming mode switch (for KNX only).
DIP & Rotary Switches	EIA-485 serial port configuration.
Contains Battery	No

Certifications and Standards

Product Certifications	CE, CB, UKPSTI, UL
WEEE Category	IT and telecommunications equipment

Mitsubishi Electric City Multi systems to Modbus TCP/RTU Application

Use Case



Integration example.

Use Intesis MAPS to change the protocol: BACnet, Modbus, KNX, MQTT, or Home Automation