

Hitachi VRF systems to KNX Application

Item number: IN770AIR00SO000

This gateway allows the integration of Hitachi VRF and air-to-water systems into KNX TP control systems. A single gateway can integrate up to 16 indoor units.



Hitachi to KNX - up to 16 indoor units

Features and benefits

- ✓ **Integration of VRF, Yutaki, and Yutampo models on the same bus**
Simplify system design and reduce commissioning time and costs by eliminating the need for model-specific gateways.
- ✓ **Connection to the outdoor unit**
Avoid complex and expensive wiring: one gateway connected to a single outdoor unit enables individualized control of its indoor units.
- ✓ **Dedicated signals for error and maintenance monitoring**
Quickly realize what's wrong and anticipate problems to prevent downtime and extend the HVAC system's lifespan.
- ✓ **Configuration using Intesis MAPS**
Reduce configuration time by importing and reusing preset templates.
- ✓ **KNX thermostat**
Read the room temperature from either the indoor unit or a KNX thermostat.
- ✓ **HVAC bus scanning function**
Accelerate commissioning and avoid manual mapping errors by automatically discovering and importing all units, including their variables.
- ✓ **Individual indoor unit energy consumption signals**
Reduce energy costs through HVAC system performance analysis and energy hotspots detection.
- ✓ **Outdoor unit monitoring**
Extend your project's capabilities by incorporating outdoor unit signals.
- ✓ **CSNET Manager and PSC-6RAD adapter supported**
Provide maximum flexibility for your project.
- ✓ **Designed in collaboration with Hitachi and certified by UL**
Ensure reliability in professional building automation environments.



General	
Capacity	S: Up to 16 indoor units
Net Width (mm)	106
Net Height (mm)	90
Net Depth (mm)	58
Net Weight (g)	194
Packed Width (mm)	125
Packed Height (mm)	85
Packed Depth (mm)	140
Packed Weight (g)	356
Operating Temperature °C Min	0°
Operating Temperature °C Max	60°
Storage Temperature °C Min	-30
Storage Temperature °C Max	60
Power Consumption (W)	3
Input Voltage (V)	For DC: 12 .. 36 VDC ±10%, Max: 250 mA For AC: 24 VAC ±10 %, 50-60 Hz, Max: 127 mA Recommended voltage: 24 VDC, Max: 127 mA
Power Connector	3-pole
Configuration	Intesis MAPS
Installation Conditions	This gateway is designed to be mounted inside an enclosure. If the unit is mounted outside an enclosure, precautions should always be taken to prevent electrostatic discharge to the unit. When working inside an enclosure (e.g., making adjustments, setting switches, etc.), typical anti-static precautions should always be followed before touching the unit.
AC Model Compatibility	Compatible with Hitachi VRF, Yutaki Series S / SCombi (lite) / S80 / M (all released from 2016), Yutampo, AIRH2O Series 600 / 800, and YCC systems.



General

Content of Delivery	Intesis gateway and installation manual.
Not Included (in delivery)	Power supply not included.
Mounting	DIN rail mount (bracket included), Wall mount
Housing Materials	Plastic
Warranty (years)	3 years
Packaging Material	Cardboard

Identification and Status

Product ID	IN770AIR00SO000_KNX_HIT
Country of Origin	Spain
HS Code	8517620000
Dual Usage	No

Physical Features


Connectors / Input / Output	Power supply, EIA-485, KNX, Ethernet, HVAC port, Binary inputs (dry contact), Console port USB.
LED Indicators	Gateway and communication status.
Push Buttons	Factory reset. I-Am message (for BACnet only). Normal mode/programming mode switch (for KNX only).
DIP & Rotary Switches	EIA-485 serial port configuration.
Contains Battery	No

Certifications and Standards


Product Certifications	CE, CB, UKPSTI, UL
WEEE Category	IT and telecommunications equipment



Use Case



Integration example.



Use Intesis MAPS to change the protocol: BACnet, Modbus, KNX, MQTT, or Home Automation