

Daikin VRV and Sky systems to BACnet MS/TP Interface

Item number: IN485DAI001R000

The Daikin-BACnet interface allows full bidirectional communication between Daikin VRV and Sky Air Conditioner units and BACnet MS/TP networks. The interface enables BACnet communication via polling or subscription requests (COV), making the indoor unit available through independent BACnet objects. A wired remote controller can also be connected.



Daikin to BACnet MS/TP - 1 indoor unit

Features and benefits

- ✓ **BACnet MS/TP and Modbus RTU supported**
The interface supports both BACnet MS/TP and Modbus RTU protocols.
- ✓ **Energy savings through a window contact function**
This function helps minimize costs, as HVAC systems are a major building energy consumer.
- ✓ **AC unit control by remote and BACnet MS/TP**
The AC unit can simultaneously be controlled via BACnet MS/TP and its own remote controller.
- ✓ **Multiple mounting options**
Mounting options include DIN rail, wall, or, in some AC models, even inside the indoor unit.
- ✓ **Dual configuration options**
The interface configuration is carried out directly through its onboard DIP switches.
- ✓ **Total unit control and monitoring from BACnet**
Through internal variables, running hours counter (for maintenance purposes), and error indication.
- ✓ **No external power required**
The interface is powered directly from the AC unit, so no external power supply is required.

Daikin VRV and Sky systems to BACnet MS/TP Interface



General	
Capacity	1 indoor unit
Net Width (mm)	53
Net Height (mm)	93
Net Depth (mm)	58
Net Weight (g)	95
Packed Width (mm)	135
Packed Height (mm)	85
Packed Depth (mm)	100
Packed Weight (g)	188
Operating Temperature °C Min	0°
Operating Temperature °C Max	70°
Storage Temperature °C Min	0
Storage Temperature °C Max	70
Power Consumption (W)	14VDC/80mA
Configuration	Dip-switches
Installation Conditions	This gateway is designed to be mounted inside an enclosure. If the unit is mounted outside an enclosure, precautions should always be taken to prevent electrostatic discharge to the unit. When working inside an enclosure (e.g., making adjustments, setting switches, etc.), typical anti-static precautions should always be followed before touching the unit.
AC Model Compatibility	Daikin VRV & Sky systems
Content of Delivery	Intesis gateway and installation manual.
Housing Materials	Plastic

Daikin VRV and Sky systems to BACnet MS/TP Interface



General	
Warranty (years)	3 years
Packaging Material	Cardboard
Identification and Status	
Product ID	IN485DAI001R000_BAC_DAI
Country of Origin	Spain
HS Code	8517620000
Dual Usage	No
Physical Features	
LED Indicators	Gateway and communication status.
Contains Battery	No
Certifications and Standards	
Product Certifications	CE, CB, UKPSTI, UL, BTL
WEEE Category	IT and telecommunications equipment



Use Case



Integration example.