

Anybus CompactCom 30 Module SERCOS III without housing



Item number: AB6322-B

The Anybus CompactCom 30 SERCOS III without housing is a communication interface that can be embedded into any industrial device or machine to enable communication with SERCOS III networks. The module version includes connectors to simplify installation, helping you achieve a fast time to market.

*Enable communication between industrial devices and
SERCOS III networks*

Features and benefits

Anybus CompactCom 30 Module SERCOS III without housing



General

Net Width (mm)	37
Net Height (mm)	16
Net Depth (mm)	51
Net Weight (g)	19
Packed Weight (g)	19
Operating Temperature °C Min	-40
Operating Temperature °C Max	85
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Class (CompactCom series)	B
Input Voltage (V)	3.3 VDC, +/- 0.15 VDC
Application Interface	8-bit parallel (30 ns access) UART (max 625kbps)
Isolation	Galvanic Isolation
Content of Delivery	CompactCom M30 module
Mounting	PCB mounting via a customized CompactFlash connector
Warranty (years)	1

Identification and Status

Product ID	AB6322-B
Country of Origin	Sweden
HS Code	8517620000

Anybus CompactCom 30 Module SERCOS III without housing



Identification and Status

Dual Usage	No
------------	----

Physical Features

Connectors / Input / Output	2x RJ45
LED Indicators	Indicates Module Status, Network Status and Link/Activity.
Form Factor	Module without Housing
Contains Battery	No

Certifications and Standards

Protection Class IP	IP20
RoHS Compliant	Yes
Product Certifications	RoHS, UL
UL Information	E214107