

Anybus CompactCom 40 Brick EtherNet/IP

Item number: AB6674-D

The Anybus CompactCom 40 EtherNet/IP is a communication interface that can be embedded into any industrial device or machine to enable communication with EtherNet/IP networks. The pluggable design enables integration late in the assembly process, the addition of specific network connectors, and compliance with protection class requirements.



Enable communication between industrial devices and EtherNet/IP networks

Features and benefits

- ✓ **High performance**
Powered by the award-winning NP40 network processor, the Anybus CompactCom guarantees fast data transfer and low latency, making it ideal for the most demanding industrial applications.
- ✓ **Quick time to market**
HMS provides comprehensive support throughout the integration journey, ensuring a quick time to market.
- ✓ **Life cycle management**
HMS maintains every part of the Anybus CompactCom, including network updates, throughout the product's lifecycle.
- ✓ **Fully embedded – meet IP requirements**
The brick can be fully embedded within your product, conserving valuable space, and enabling you to provide IP class-certified protection.
- ✓ **Supports hardware changes**
Possible to swap or install late in the manufacturing process.
- ✓ **Versatile Event-Based Hardware Interfaces**
Enjoy fast and flexible event-based application hardware interfaces with the option to choose from 8/16-bit parallel or high-speed SPI, and I/O via the shift register interface.
- ✓ **ODVA pre-certified**
Pre-certified with ODVA for network compliance, enabling faster network certification.
- ✓ **Design flexibility**
Add your own connectors and peripherals, offering design flexibility that matches your unique needs.
- ✓ **Robust Security Measures**
Mandatory software signatures prevent unauthorized downloads to the Anybus CompactCom, while robust encryption techniques safeguard against illicit copying.

Anybus CompactCom 40 Brick EtherNet/IP



General

Related Accessories	AB6666-B
Net Width (mm)	36
Net Height (mm)	8
Net Depth (mm)	36
Net Weight (g)	20
Packed Width (mm)	8
Packed Height (mm)	3
Packed Depth (mm)	8
Packed Weight (g)	20
Operating Temperature °C Min	-40
Operating Temperature °C Max	85
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Class (CompactCom series)	B
Current Consumption Max value at Vcc nom (mA)	up to 500 mA
Input Voltage (V)	3.3 VDC, +/- 0.15 VDC
Application Interface	Parallel 8/16-bit (30 ns access). High speed SPI (baudrate configurable up to 50 MHz). Shift register interface (cyclical update time 82 µs). UART (for backwards compatibility with 30-series, max 625kbps).
Content of Delivery	CompactCom B40 module
Mounting	PCB mounting via pin header

Anybus CompactCom 40 Brick EtherNet/IP



General

Warranty (years)	1 year
------------------	--------

Identification and Status

Product ID	AB6674-D
Predecessor	AB6674-C
Country of Origin	China
HS Code	8517620000
Dual Usage	No

Physical Features

Form Factor	Brick (pluggable)
Contains Battery	No

EtherNet/IP Features

EtherNet/IP Mode	Generic Device
EtherNet/IP Supported Functionality	Beacon Based DLR (Device Level Ring) and linear network topology supported. CIP Sync functionality. Web server w. customizable content. FTP server. Email client. Server Side Include (SSI) functionality. JSON functionality. CIP Parameter Object support. Supports unconnected CIP routing. Transparent Socket Interface. QuickConnect supported. Link Layer Discovery Protocol.
EtherNet/IP Configuration File	EDS available
EtherNet/IP Bandwidth	10/100 Mbit/s
EtherNet/IP Input Data Size	1448 bytes
EtherNet/IP Output Data Size	1448 bytes

Certifications and Standards

RoHS Compliant	Yes
Product Certifications	RoHS, UL
UL Information	E214107