

Anybus CompactCom 40 Module Without Housing - POWERLINK



Item number: AB6711-E

The Anybus CompactCom 40 Without Housing - POWERLINK is a communication interface that can be embedded into any industrial device or machine to enable communication with POWERLINK networks. The module version includes connectors to simplify installation, helping you achieve a fast time to market.

Enable communication between industrial devices and POWERLINK networks

Features and benefits

- ✓ **High performance**
Powered by the award-winning NP40 network processor, the Anybus CompactCom guarantees fast data transfer and low latency, making it ideal for the most demanding industrial applications.
- ✓ **Quick time to market**
HMS provides comprehensive support throughout the integration journey, ensuring a quick time to market.
- ✓ **Life cycle management**
HMS maintains every part of the Anybus CompactCom, including network updates, throughout the product's lifecycle.
- ✓ **Custom look**
Delivered without housing, enabling the Anybus CompactCom to be securely integrated behind the front panel of your device, resulting in a customized appearance and seamless design integration.
- ✓ **Supports hardware changes**
Possible to swap or install late in the manufacturing process.
- ✓ **Versatile Event-Based Hardware Interfaces**
Enjoy fast and flexible event-based application hardware interfaces with the option to choose from 8/16-bit parallel or high-speed SPI, and I/O via the shift register interface.
- ✓ **POWERLINK pre-certified**
Pre-certified with POWERLINK for network compliance, enabling faster network certification.
- ✓ **Complete communication interface**
The Anybus CompactCom module is a complete communication interface, equipped with connectors that simplify integration. Enjoy an all-in-one solution with easy interchangeability.
- ✓ **Robust Security Measures**
Mandatory software signatures prevent unauthorized downloads to the Anybus CompactCom, while robust encryption techniques safeguard against illicit copying.

Anybus CompactCom 40 Module Without Housing - POWERLINK



General

Net Width (mm)	37
Net Height (mm)	16
Net Depth (mm)	51
Net Weight (g)	18
Packed Weight (g)	18
Operating Temperature °C Min	-40
Operating Temperature °C Max	85
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Class (CompactCom series)	B
Current Consumption Max value at Vcc nom (mA)	up to 500 mA
Input Voltage (V)	3.3 VDC, +/- 0.15 VDC
Application Interface	Parallel 8/16-bit (30 ns access). High speed SPI (baudrate configurable up to 50 MHz). Shift register interface (cyclical update time 82 µs). UART (for backwards compatibility with 30-series, max 625kbps).
Isolation	Galvanic Isolation
Content of Delivery	CompactCom M40 module (without housing)
Mounting	PCB mounting via a CompactFlash connector
Warranty (years)	1 year

Identification and Status

Product ID	AB6711-E
Predecessor	AB6711-C, AB6711-D

Anybus CompactCom 40 Module Without Housing - POWERLINK



Identification and Status

Country of Origin	Sweden
HS Code	8517620000
Dual Usage	No

Physical Features

Connectors / Input / Output	2x RJ45
LED Indicators	Semi-Integrated. Link/Activity are available on RJ45 connectors. Module Status and Network Status via application interface or external light pipes
Form Factor	Module without Housing
Contains Battery	No

POWERLINK Features

POWERLINK Mode	Generic device
POWERLINK Supported Functionality	Ethernet POWERLINK V2.0 Communication Profile Specification version 1.3.0 (Controlled Node, CN). Integrated hub. Web server w. customizable content. FTP server. Email client. Server Side Include (SSI) functionality. JSON functionality. Transparent Socket Interface. Supports ring redundancy. Supports segmented SDO transfer. PollResponse Chaining. Multiplexing. Support for Dynamic Node Allocation (DNA).
POWERLINK Configuration File	XDD available
POWERLINK Bandwidth	100 Mbit/s half duplex
POWERLINK Input Data Size	1490 bytes
POWERLINK Output Data Size	1490 bytes

Certifications and Standards

RoHS Compliant	Yes
UL Information	E214107