



Anybus Communicator – Serial Master to Lonworks

Item number: AB7009-B

The Anybus Communicator – Serial Master to Lonworks converts serial protocols to Lonworks, enabling you to connect any RS-232/422/485 device or equipment to Lonworks control systems. Anybus Communicators ensure reliable, secure, high-speed data transfers between different industrial networks while being easy to use.



A protocol converter that connects serial devices to Lonwork control systems.

Features and benefits



Anybus Communicator – Serial Master to Lonworks

General

Net Width (mm)	27
Net Height (mm)	120
Net Depth (mm)	75
Net Weight (g)	400
Packed Width (mm)	17
Packed Height (mm)	9
Packed Depth (mm)	19
Packed Weight (g)	750
Operating Temperature °C Min	0
Operating Temperature °C Max	55
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Relative Humidity	0-95% non condensing
Current Consumption Type Value at Vcc Nom (mA)	100mA @ 24V DC
Current Consumption Max value at Vcc nom (mA)	300mA @ 24V DC
Input Voltage (V)	24V DC (-10% to +10%)
Power Connector	2-pin, 5.08 Phoenix plug connector
Reverse Polarity Protection	Yes
Short Circuit Protection	Yes



Anybus Communicator – Serial Master to Lonworks

General

Isolation	TRUE
Maximum Installation Altitude (m)	up to 2 000 m
Mounting	DIN-rail (EN 50022 standard)
Housing Materials	PC ABS, UL 94
Packaging Material	Cardboard

Identification and Status

Product ID	AB7009-B
Country of Origin	Sweden
HS Code	8517620000
Dual Usage	No

Physical Features

Connectors / Input / Output	1x D-sub 9-pin female
Contains Battery	No

Modbus-RTU Features

Modbus-RTU Mode	Client / Master
Modbus-RTU Supported Functionality	RS-232; RS-422; RS485; DF1; Standard Modbus RTU Master; Custom Request / Response commands; Custom Produce / Consume transactions; Trigger initiated transactions 7 or 8 data bit; None, Odd, Even Parity; 1 or 2 stop bit; Clear/Freeze
Modbus-RTU Functions Supported	1, 2, 3, 4, 5, 6, 7, 8, 11, 12, 15, 16, 17, 20, 21, 22, 24
Modbus-RTU Baud Rate	1200,1800,2400,4800,7200,9600,14400,19200,35700,38400,57600 bit/s
Modbus-RTU Input Data Size	512 bytes
Modbus-RTU Output Data Size	512 bytes

Serial Features

Connector	1x D-sub 9-pin female
Max Nodes	31



Anybus Communicator – Serial Master to Lonworks

Serial Features

Baud Rate	1200,1800,2400,4800,7200,9600,14400,19200,35700,38400,57600 bit/s
Supported Functionality	RS-232; RS-422; RS485; DF1; Standard Modbus RTU Master; Custom Request / Response commands; Custom Produce / Consume transactions; Trigger initiated transactions 7 or 8 data bit; None, Odd, Even Parity; 1 or 2 stop bit; Clear/Freeze

Certifications and Standards

Protection Class IP	IP20
RoHS Compliant	Yes
Recycle / Disposal	TRUE
Product Certifications	CE, UL, WEEE
UL Information	E214107: Ord.Loc UL508, CSA C22.2 No. 14-10; E203225: Haz.Loc CL I DIV2 GP A,B,C,D, ANSI/ISA 12.12.01, CSA C22.2 No. 213
Environment	EN 50082-2, EN 55011, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6
WEEE Category	IT and telecommunications equipment