



Anybus Communicator – Serial Master to EtherNet/IP

Item number: AB7007-C

The Anybus Communicator – Serial Master to EtherNet/IP converts serial protocols to EtherNet/IP, enabling you to connect any RS-232/485 device or equipment to EtherNet/IP control systems. Anybus Communicators ensure reliable, secure, high-speed data transfers between different industrial networks while being easy to use.



A protocol converter that connects serial devices to EtherNet/IP control systems.

Features and benefits

Anybus Communicator – Serial Master to EtherNet/IP



General

Net Width (mm)	27
Net Height (mm)	120
Net Depth (mm)	75
Net Weight (g)	150
Packed Width (mm)	135
Packed Height (mm)	55
Packed Depth (mm)	170
Packed Weight (g)	300
Operating Temperature °C Min	0
Operating Temperature °C Max	55
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Relative Humidity	0-95% non condensing
Current Consumption Type Value at Vcc Nom (mA)	100mA @ 24V DC
Current Consumption Max value at Vcc nom (mA)	300mA @ 24V DC
Input Voltage (V)	24V DC (-10% to +10%)
Power Connector	2-pin, 5.08 Phoenix plug connector
Reverse Polarity Protection	Yes
Short Circuit Protection	Yes

Anybus Communicator – Serial Master to EtherNet/IP



General

Isolation	TRUE
Maximum Installation Altitude (m)	up to 2 000 m
Mounting	DIN-rail (EN 50022 standard)
Housing Materials	PC ABS, UL 94
Packaging Material	Cardboard

Identification and Status

Product ID	AB7007-C
Successor	ABC3007-A
Country of Origin	Sweden
HS Code	8517620000
Dual Usage	No

Physical Features

Connectors / Input / Output	1x D-sub 9-pin female, 1xRJ45
DIP & Rotary Switches	8 Dip switches for IP settings
Contains Battery	No

EtherNet/IP Features

EtherNet/IP Mode	Adapter / Slave
EtherNet/IP Supported Functionality	DLR; QoS; EtherNet/IP Adapter Level 2 and Level 3 I/O Server CIP
EtherNet/IP Configuration File	EDS available
EtherNet/IP Bandwidth	10/100MBit
EtherNet/IP Input Data Size	509 bytes
EtherNet/IP Output Data Size	505 bytes

Anybus Communicator – Serial Master to Ethernet/IP



Modbus-RTU Features

Modbus-RTU Mode	Client / Master
Modbus-RTU Supported Functionality	RS-232; RS-422; RS485; DF1; Standard Modbus RTU Master; Custom Request / Response commands; Custom Produce / Consume transactions; Trigger initiated transactions 7 or 8 data bit; None, Odd, Even Parity; 1 or 2 stop bit; Clear/Freeze
Modbus-RTU Functions Supported	1, 2, 3, 4, 5, 6, 7, 8, 11, 12, 15, 16, 17, 20, 21, 22, 24
Modbus-RTU Baud Rate	1200,1800,2400,4800,7200,9600,14400,19200,35700,38400,57600 bit/s
Modbus-RTU Input Data Size	512 bytes
Modbus-RTU Output Data Size	512 bytes

Serial Features

Connector	1x D-sub 9-pin female
Max Nodes	31
Baud Rate	1200,1800,2400,4800,7200,9600,14400,19200,35700,38400,57600 bit/s
Supported Functionality	RS-232; RS-422; RS485; DF1; Standard Modbus RTU Master; Custom Request / Response commands; Custom Produce / Consume transactions; Trigger initiated transactions 7 or 8 data bit; None, Odd, Even Parity; 1 or 2 stop bit; Clear/Freeze

Certifications and Standards

Protection Class IP	IP20
RoHS Compliant	Yes
Recycle / Disposal	TRUE
Product Certifications	CE, UL, WEEE
UL Information	E214107: Ord.Loc UL508, CSA C22.2 No. 14-10; E203225: Haz.Loc CL I DIV2 GP A,B,C,D, ANSI/ISA 12.12.01, CSA C22.2 No. 213
Environment	EN 50082-2, EN 55011, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6
WEEE Category	IT and telecommunications equipment